

# MULTI+ 35

Find individual luminaires

quickly and easily [Code finder](#)[Clear filters](#)

Which category would you like to search for?

- ☐ DISCOVER 
- ☐ BOOST 
- ☐ ELEVATE 

- Series 
- Colour temperature [K] 
- CRI 
- Optic 
- Distribution of light emission 
- Luminaire lumen output [lm] 
- Luminaire wattage [W] 
- Luminous efficacy [lm/W] 
- Voltage type 
- Colour 
- Finishing 



Presentation  Projects  Download 

Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:

- Technopolymer housing
- Technopolymer vandal-proof opal diffuser, 960°C glow wire test rated
- Anti-ageing custom moulded silicone sealing gasket(s)
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Stainless steel, anti-tampering locking screws
- Through-wiring designed
- Class II
- Max 20 mm diameter for cable/conduit entry
- EM/1P are maintained emergency versions (1h)
- Twilight models (C versions) are complete with dusk sensor

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

- ▶ Light controls ✓
- ▶ Sensors ✓
- ▶ Emergency luminaire ✓
- ▶ IP degree of protection ✓
- ▶ Mechanical impact protection code IK ✓
- ▶ Protection class ✓
- ▶ Electrical connections ✓
- ▶ Min. ambient temperature [°C] ✓
- ▶ Max. ambient temperature [°C] ✓
- ▶ UGR - Unified Glare Rating ✓
- ▶ MOQ ✓



## MULTI+ 35

Optic | Symmetric Extra-Wide



Product List ▼ Accessories ▼ Sources ▼



## MULTI+ 35/C

Optic | Symmetric Extra-Wide



Product List ▼ Accessories ▼ Sources ▼



## MULTI+ 35 EM/1P

Optic | Symmetric Extra-Wide



Product List ▼ Accessories ▼ Sources ▼

# Product Family



MULTI+ 30 PC



MULTI+ 40 PC

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>



**GEWISS** LightZone

Since 2023, Performance iN Lighting has been part of the GEWISS Group, within the GEWISS LightZone ecosystem, where we develop integrated lighting solutions that transform complexity into simplicity, supporting professionals and end users in meeting their needs.

Discover more on GEWISS

Products

Indoor lighting  
Outdoor lighting

Projects

Office  
Retail  
Healthcare  
Hospitality  
Industry  
Residential  
City Landscape  
Sports  
Transportation

Service & Downloads

Technical Customer Support  
Lighting Technical Solutions  
Bespoken lighting solutions  
Norms and regulations  
LIGHT-PERFORMER®  
dimSMART!®  
SMART  
Design instruments  
Downloads

Company

Who we are  
Warranty  
General sales conditions  
Sustainability at the center of the future  
Governance  
Sales network  
Contact us  
Work with us