

MULTI+ 30 PC

Find individual luminaires

quickly and easily [Code finder](#)[Clear filters](#)

Which category would you like to search for?

- ☐ DISCOVER 
- ☐ BOOST 
- ☐ ELEVATE 



- Series 
- Colour temperature [K] 
- CRI 
- Optic 
- Distribution of light emission 
- Luminaire lumen output [lm] 
- Luminaire wattage [W] 
- Luminous efficacy [lm/W] 
- Voltage type 
- Colour 
- Finishing 

[Presentation](#) 
[Projects](#) 
[Download](#) 

Series of wall and ceiling mounted luminaires for indoor and outdoor use, comprising:

- Technopolymer housing
- Technopolymer vandal-proof opal diffuser, 960°C glow wire test rated
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel, anti-tampering locking screws
- Through-wiring designed
- Integral, tiltable, self-heat dissipating, Metal-Core SMD LED board (future proof)
- Class II
- Built-in driver
- Max 20 mm diameter for cable/conduit entry
- EM/3P version is designed for multipurpose 3 hours sustained

To maintain the regular updating of our products, PERFORMANCE IN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

- ▶ **Light controls** ✓
- ▶ **Sensors** ✓
- ▶ **Emergency luminaire** ✓
- ▶ **IP degree of protection** ✓
- ▶ **Mechanical impact protection code IK**
- ▶ **Protection class** ✓
- ▶ **Electrical connections** ✓
- ▶ **Min. ambient temperature [°C]** ✓
- ▶ **Max. ambient temperature [°C]** ✓
- ▶ **UGR - Unified Glare Rating** ✓
- ▶ **MOQ** ✓


emergency lighting

- Hyper-frequency (HF) sensor operating at 5.8 Ghz+/- 75 Mhz
- SMART versions are equipped with customised electronic devices that allow energy savings reducing the luminous flux, whilst providing a 30% working flux for safety lighting and reaching 100% flux when necessary
- SMART HF versions are complete with integrated High Frequency (HF) sensor that operates from 30% up to 100% of the flux when it detects the presence of people
- SMART DA versions are suitable for use in systems with two separate lines where the demand for 100% of the flux is managed by a push button or line sensor



MULTI+ 30 PC

Optic | Symmetric Extra-Wide



Product List ▼ Accessories ▼ Sources ▼



MULTI+ 30 PC HF

Optic | Symmetric Extra-Wide



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/gr/company/led-warranty>



Product List ▾ Accessories ▾ Sources ▾

Newsletter



MULTI+ 30 PC EM/3P

Optic | Symmetric Extra-Wide



Product List ▾ Accessories ▾ Sources ▾

Product Family



MULTI+ 40 PC



MULTI+ 35

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>


For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com



Newsletter Subscribe

Request information



GEWISS LightZone

Since 2023, Performance iN Lighting has been part of the GEWISS Group, within the GEWISS LightZone ecosystem, where we develop integrated lighting solutions that transform complexity into simplicity, supporting professionals and end users in meeting their needs.

[Discover more on GEWISS](#)

Products

Indoor lighting
Outdoor lighting

Projects

Office
Retail
Healthcare
Hospitality
Industry
Residential
City Landscape
Sports
Transportation

Service & Downloads

Technical Customer Support
Lighting Technical Solutions
Bespoken lighting solutions
Norms and regulations
LIGHT-PERFORMER®
dimSMART!®
SMART
Design instruments
Downloads

Company

Who we are
Warranty
General sales conditions
Sustainability at the center of the future
Governance
Sales network
Contact us
Work with us

International/English Downloads

© 2026 Performance in Lighting S.p.A. sole shareholder company | Subject to the direction and coordination of Gewiss S.p.A. | P.Iva: 08517220011 - [Privacy Policy](#) - [Cookie Policy](#) - [Accessibility Statement](#)

