

STB 30.5 IH/GE**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| | |
|---------------------|---|
| Version | Socket (terminal), Plug-in depth: 10 mm, Depth: 31.7 mm |
| Order No. | 0341500000 |
| Type | STB 30.5 IH/GE |
| GTIN (EAN) | 4008190130961 |
| Qty. | 50 items |
| Delivery status | This article will no longer be available in the future. |
| Available until | 2026-06-30T00:00:00+02:00 |
| Alternative product | STB 30.5 IH/RT |

STB 30.5 IH/GE

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|----------|---------|----------------|-------------|
| Depth | 31.7 mm | Depth (inches) | 1.248 inch |
| Width | 7.2 mm | Width (inches) | 0.2835 inch |
| Diameter | 7.2 mm | Net weight | 2.52 g |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|----------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -50 °C...55 °C |
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | dce63e23-eea1-4eaa-9071-1c98fc8fa2ea |

Material data

| | | | |
|---------------------------|-------|--------|--------|
| Basic material | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-2 | | |

System specifications

| | |
|---------|------------------------|
| Version | For the mounting rails |
|---------|------------------------|

Additional technical data

| | | | |
|------------------|-----------------|--------------------------|----|
| Type of fixing | when screwed in | Explosion-tested version | No |
| Type of mounting | when screwed in | | |

Dimensions

| | | | |
|---------------|--------|------------------|------|
| Diameter | 7.2 mm | Length of thread | 7 mm |
| Plug-in depth | 10 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002848 | ETIM 9.0 | EC002848 |
| ETIM 10.0 | EC002848 | ECLASS 14.0 | 27-25-03-90 |
| ECLASS 15.0 | 27-25-03-90 | | |