
























| | | | |
|---|---|---|---|
| **EAN:** | 4013288234063 | **Size:** | 190x135x55 mm |
| **Part number:** | 05051531001 | **Weight:** | 545 g |
| **Article number:** | Kraftform Kompakt 60 RA-R Imperial 1 | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82054000 |

- The ratchet with fine toothing integrated in the handle allows fast working
- The innovative ratchet mechanism also allows fast "spinning". A real problem solver when there is no resistance from the screw
- Intuitive switching: If I turn the switch clockwise - the ratchet turns clockwise, if I turn the switch counterclockwise - it goes counterclockwise
- Use position 0 to deactivate the ratchet mechanism for precise working
- Innovative Rapidaptor technology for a quick bit change
- 16 bits, 89 mm long, for Phillips, TORX® BO, hexagonal socket, square head and slotted
- In a robust folding pouch with Wera 2go compatibility

17-piece set with 89 mm long bits in a practical folding pouch. Includes one 838 RA-R L bitholding screwdriver with ratchet functionality. The ratchet with fine toothing integrated in the handle allows fast working. The innovative ratchet mechanism allows "spinning" when the screw offers little resistance. Switching the screwdriving direction is intuitive: Turn the ring switch clockwise for clockwise screwdriving, turn it counterclockwise for counterclockwise screwdriving. Use position 0 to deactivate the ratchet mechanism for precise working. The Rapidaptor quick-release chuck (suitable for bits with 1/4" external hexagon drive as per DIN ISO 1173-C 6.3 and E 6.3 (ISO 1173)) allows for lightning-fast bit changes without any extra tools. 16 bits (89 mm), tough, for universal use.

**Web link**
https://www.wera.de/en/05051531001



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

### Ratchet mechanism in the handle



The integrated ratchet with fine toothing ensures fast and safe working. The ratchet mechanism is completely embedded in the handle.

### Intuitive screwdriving



Switching the screwdriving direction is intuitive: Turn the ring switch clockwise for clockwise screwdriving, turn it counterclockwise for counterclockwise screwdriving.

### Ratchet mechanism allows fast spinning



The innovative ratchet mechanism allows "spinning" when the screw offers little resistance.

### Chuck-all




The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

### Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

### Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

### Handle/interchangeable blade system



The handle/interchangeable blade system allows rapid exchange of the blades required for a wide range of applications.

### Kraftform



The basic idea for the prototype of the Kraftform handle - that the hand should dictate the design - has, right through to today, proved to be correct. In cooperation with the internationally recognised Fraunhofer IAO Institute, Wera developed a screwdriver handle designed to match the shape of the human hand as long ago as the 1960s. After a long development phase, the Wera Kraftform handle was launched to the market in 1968. It has been optimised through the years with new technologies, but has kept its proven shape. After all, the human hand has not changed either.

**Web link**
https://www.wera.de/en/05051531001

Wera - Kraftform Kompakt 60 RA-R Imperial 1
05051531001 - 4013288234063

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Set contents:

## 838 RA-R L Bitholding screwdriver with ratchet functionality, 1/4", 1/4" x 140 mm



| | | |
|---|---|---|
| 05051494001 | 1x | 1/4" x 140 mm |

## 851/4 Z bits, PH 1 x 89 mm



| | | |
|---|---|---|
| 05059760001 | 1x | PH 1 x 89 mm |
| 05059775001 | 1x | PH 2 x 89 mm |
| 05059795001[1)] | 1x | PH 3 x 89 mm |

1) Hexagonal blade

## 867/4 Z TORX® BO bits with bore hole, TX 10 x 89 mm



| | | |
|---|---|---|
| 05060050001 | 1x | TX 10 x 89 mm |
| 05060051001 | 1x | TX 15 x 89 mm |
| 05060052001 | 1x | TX 20 x 89 mm |
| 05060053001 | 1x | TX 25 x 89 mm |
| 05060054001 | 1x | TX 30 x 89 mm |

## 840/4 Z bits, 3/32" x 89 mm



| | | |
|---|---|---|
| 05059661001 | 1x | 3/32" x 89 mm |
| 05059663001 | 1x | 1/8" x 89 mm |
| 05059665001 | 1x | 5/32" x 89 mm |
| 05059666001 | 1x | 3/16" x 89 mm |

## 868/4 Square-Plus bits, # 1 x 89 mm



| | | |
|---|---|---|
| 05134800001 | 1x | # 1 x 89 mm |
| 05134801001 | 1x | # 2 x 89 mm |
| 05134802001 | 1x | # 3 x 89 mm |

## 800/4 Z bits, 1 x 5.5 x 89 mm



| | | |
|---|---|---|
| 05059488001 | 1x | 1 x 5.5 x 89 mm |

**Web link**
https://www.wera.de/en/05051531001



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de