Reinforcement adapter

IBT BWA



IBT BWA

Reinforcement adapter

Productnumber: 97933001
Dimensions: 76 x 300 x 35 mm

Reinforcement adapter, suitable for taking all U71 sockets (except for Perilex), combinable with a standard spacing of 71 mm, face concrete for opposing formwork without support with preinstallation in the reinforcement for concrete construction, Halogen free

installation at reinforcement via reinforcement adapter

Technical Data

electrical characteristics

Suitable for:	Concrete construction

Colours

Cover colour:	grey

Dimensions

Width:	76 mm
Length:	300 mm
Height:	35 mm
Weight:	0.0658 kg

Material characteristics

Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	installation at reinforcement via reinforcement adapter

Ambient conditions

max. relative humidity 25°C:	- %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Sales Information

EAN:	4013902456192
ETIM Class:	EC002328
Custom tariff number:	39269097

Sales Information

Minimum order quantity:	25

Material

Base unit material:	Polypropylene