
date: 27/10/2026

EB+ 431

Part number LTY1151DA930





IP 20 | CLASS II | CRI 90 | ULR<1 | CIEn°3>95 | DALI | CE | UKCA

Description

Recessed LED luminaire for indoor, comprising:
- Die-cast aluminium spotlight body and ring, powder-coated
- Reflector can be swivelled horizontally inwards and outwards thanks to the unique swivel mechanism
- Adjustable about 60° (from -15° up to 45°, rotatable about 355°
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Colour rendering index Ra > 90
- Quick and toolless installation
- Built-in driver
- Anchor springs
- Clear safety glass
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001744

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	1286	**Luminaire lumen output [lm]:**	950
Luminaire wattage [W]:	9 W	**Luminous efficacy [lm/W]:**	106
CRI:	90	**Colour temperature [K]:**	3000
Colour / Finishing:	WH-RAL9010 / White RAL9010 / Textured	**IP degree of protection:**	IP20
Impact resistance / impact energy:	IK02 0.2J xx0	**Protection class:**	II
Optic:	C/I - Circular Intensive	**Net weight [kg]:**	0.259
Overall diameter [mm]:	85	**Overall height [mm]:**	65
Cut-out diameter [mm]:	Ø 75		

Mechanical features

Shape:	Round ≤ 150 mm	**Housing material:**	Aluminium
Diffuser material:	Transparent glass	**Glow wire test [°C]:**	650 °C

Electrical features

Voltage type:	AC/DC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	>0.9
Input voltage [V DC]:	176/280	**Inrush current [A/µs]:**	30 / 100
C10 1.5 mm²:	46	**C16 2.5 mm²:**	75
B10 1.5 mm²:	27	**B16 2.5 mm²:**	45

Installation

Application area:	Indoor lighting	**Mounting type:**	Downlight and spotlight
Min. ambient temperature [°C]:	-20	**Max. ambient temperature [°C]:**	30
Min. distance from lighted object [m]:	0.10		

Light features


MacAdam:	3	**Lumen maintenance:**	L90B10@110000h
Distribution of light emission:	Direct	**DFF - Downward Flux Fraction [%]:**	0
UFF - Upward Flux Fraction [%]:	100	**Luminous Intensity Class:**	G*6
Zero light pollution (ULR = 0%):			

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com