Terminal block enclosure

RKKi 4/12-12x4²



RKKi 4/12-12x4²

Terminal block enclosure

CUSTOMIZABLE

Productnumber: 63040401
Dimensions: 110 x 110 x 66 mm

Terminal block enclosure, protection class IP54/IP66, nominal cross-section 4 mm², Ui=400V AC, Polycarbonate, internal fixing points, for installations in industrial environments and protected outdoor areas

equipped with 12-pole terminal block 4mm² (Contaclip BKA 4 type)

Accessories supplied:
4 attachment bushes IP54 M20 seal range 8 - 13,5 mm

IP54 IP66 | 4² | IK08 | 400V AC | halogen-free

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	4 mm²
Protection class:	II
Type of protection:	IP54/IP66
UL Type Rating:	not specified

Dimensions

Width:	110 mm
Length:	110 mm
Height:	66 mm
Weight:	0.31 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK08
Sealable:	yes
Stackable:	yes
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C

Ambient conditions

24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902572786
ETIM Class:	EC002713
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

19000101 - HBA - Mounting material

19000201 - ASS-kl - External hinge set

19202001 - KS M20 - Combi set

19202501 - KS M25 - Combi set

19202601 - KS M25-gro - Combi set

19400101 - TK ABL - External fixing lugs kit

89602901 - KTB 1-100 - Cable tray fastening

Cable gland

