


PVN PCBA 1KV 6I6O SPD T1+2 F**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**General ordering data**

Version	Photovoltaics, PCB, Combiner Box, 1000 V, 1 MPP, 6 Inputs / 6 Outputs per MPP, With fuse holder, Surge protection I / II
Order No.	2770540000
Type	PVN PCBA 1KV 6I6O SPD T1+2 F
GTIN (EAN)	4064675029625
Qty.	1 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2024-12-31

PVN PCBA 1KV 6I60 SPD T1+2 F
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com
Technical data
Dimensions and weights

Depth	254 mm	Depth (inches)	10 inch
Height	87.1 mm	Height (inches)	3.429 inch
Width	440 mm	Width (inches)	17.323 inch
Net weight	2,325 g		

Temperatures

Ambient temperature	-40 °C...70 °C
---------------------	----------------

Approvals and norms

Approvals	EN 61439-2, IEC 61439-2
-----------	-------------------------

Electrical characteristics

Current per Maximum Power Point, max. 90 A	
Rated DC voltage	1,000 V
Rated short-term current resistance	Rated current 112.5 A

Enclosure

Insulating material	Polyester glass-fibre reinforced, Polycarbonate	Type of mounting	4 screws
---------------------	---	------------------	----------

General data

Protection degree	IP00	Standards	EN 61439-2:2011, IEC 61439-2 ed 2.0
-------------------	------	-----------	-------------------------------------

Inputs

Amount of maximum power points (MPP)	1		
Cartridge fuse	10 x 38 mm		
DC Input + & -	Wire connection	Type of connection	PUSH IN with actuator
		Compatible cable crossection	TÜV 2 Pfg 1169/08.07
		Wire cross-section, min.	2.5 mm ²
		Wire cross-section, max.	50 mm ²
Fuse type	Empty fuse holder		
Fuse-link standard	gPV (EN 60269-6), IEC 60269-1, IEC 60269-6		
Max. number of DC inputs	per Maximum Power Point 6 inputs connected in parallel		
Number of string inputs per MPP	≥ 4...≤ 6		
Surge protection auxiliary contact	Wire connection	Type of connection	Tension clamp connection with actuator
		Flexible, max. H05(07) V-K	1.5 mm ²
		w. wire end ferrule, DIN 46228 pt 1, max.	1.5 mm ²
Number of inputs	6		

PVN PCBA 1KV 6I60 SPD T1+2 F

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Outputs

DC Output + & -	Wire connection	Compatible cable crosssection	TÜV 2 Pfg1 169/08.07
		Wire cross-section, min.	2.5 mm²
		Wire cross-section, max.	16 mm²
Max. number of DC outputs		per Maximum Power Point 7 outputs connected in parallel	

Surge protection DC side

Discharge current I_n (8/20 μ s)	20 kA	Discharge current, max. (8/20 μ s)	40 kA
Lightning test current I_{imp} (10/350 μ s)	6.25 kA	PV system voltage, max. U_{cpv}	1,100 V
Protection level U_p (+/-, -/PE, +/-PE)	≤ 3.8 kV	Protection level U_p (+/-)	≤ 3.8 kV
Protection level U_p (+/PE)	≤ 3.8 kV	Protection level U_p (-/PE)	≤ 3.8 kV
Requirements class	Type I/II	Short-circuit current I_{SCP}	11,000 A
Standards	EN 61439-2:2011, IEC 61439-2 ed 2.0	Standby power consumption P_c	<0.2 W
Total discharge current I_{total} (8/20 μ s)	50 kA	Total discharge current I_{total} (10/350 μ s)	12.5 kA

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ETIM 8.0	EC003857	ETIM 9.0	EC003857
ETIM 10.0	EC003857	ECLASS 9.0	22-57-92-03
ECLASS 9.1	22-57-02-90	ECLASS 10.0	22-57-02-90
ECLASS 11.0	22-57-02-92	ECLASS 12.0	22-57-02-92
ECLASS 13.0	22-57-02-92	ECLASS 14.0	22-57-02-92
ECLASS 15.0	22-57-02-92		

Environmental Product Compliance

RoHS Compliance Status	Compliant
REACH SVHC	Lead 7439-92-1
SCIP	bdab5698-6a20-4370-8e28-8810d882d01a

Approvals

Approvals



Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/
ROHS	Conform

Downloads

Technical Documentation	Drawing PVN PCBA 1KV 6I60 SPD T1+2 F
User Documentation	MANUAL PVN PCBA MULTI
Catalogues	Catalogues in PDF-format

PVN PCBA 1KV 6I6O SPD T1+2 F

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

