


date: 23/10/2026

INSERT+ 1 V

Part number 3118535







IP 65 | CLASS I

Description

Wall recessed luminaire, for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Inner satin toughened flat glass diffuser
- Anti-ageing custom moulded silicone sealing gasket(s)
- Stainless steel springs for quick connection to recessed box
- No visible screws
- Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
- Use of protection against voltage surges that may be on the electrical line is recommended in order to protect the appliances
- Recessed box to be ordered separately
- The recessed box removable cover features two integral spirit levels for installation ease
- Available for thourgh wiring as accessories. Connectors fit Ø 7 - Ø 10,5 mm and Ø 14 - Ø 17 mm cables

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC002892

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	418	**Luminaire lumen output [lm]:**	197
Luminaire wattage [W]:	4 W	**Luminous efficacy [lm/W]:**	49
CRI:	80	**Colour temperature [K]:**	4000
Colour / Finishing:	WH-87 / White / Textured	**IP degree of protection:**	IP65
Impact resistance / impact energy:	IK06 1J xx3	**Protection class:**	I
Optic:	A/EW - Asymmetric Extra-Wide	**Net weight [kg]:**	0.268
Overall length [mm]:	57	**Overall width [mm]:**	32
Overall height [mm]:	226		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Opal glass		

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	0.7
Inrush current [A/µs]:	3 / 332	**C10 1.5 mm²:**	160
C16 2.5 mm²:	256	**B10 1.5 mm²:**	100
B16 2.5 mm²:	160		

Installation

Application area:	Outdoor lighting	**Mounting type:**	Steplight
Min. ambient temperature [°C]:	-20	**Max. ambient temperature [°C]:**	45

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@65000h
Distribution of light emission:	Direct		

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Mandatory accessories

INSERT+ 1 V



310475

Recessed box INSERT+ 1

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com