

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings -your first choice for industrial housings with IP 65 protection.

General ordering data

Version	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged condition), Bulkhead housing, Sidelocking clamp on lower side, Standard
Order No.	<u>1665860000</u>
Туре	HDC 32A ABU
GTIN (EAN)	4008190871253
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dim	ensions	and	weights
	GIISIUIIS	anu	WEIGHT

Dimensions and weights			
Height	30 mm	Height (inches)	1.181 inch
Width	60.5 mm	Width (inches)	2.382 inch
Mounting dimension - height	42 mm	Mounting dimension - width	92 mm
Net weight	175 g		
Temperatures			
Limit temperature	-40 °C 125 °C		
Dimensions			
Height of base B1	7 mm	Height of housing B	30 mm
Hole pitch length A2	92 mm	Total length housing	82 mm
Width base C1	60.5 mm	Width housing C	56 mm
General data			
EMO!	N		
EMC housings Material of leaking element	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65 (in plugged condi- tion)
Surface finish	Powder coating	Tightening torque	1.2 Nm
Version			
BG	7	Clamp version	Side-locking clamp
Colour (RAL)	RAL 7035	Design	Standard
Design of housing	Bulkhead housing	Design of locking system	Side-locking clamp on lover side
Sealing	NBR	Size	7
Suitable for ModuPlug [®]	No	Tightening torque	1.2 Nm
Top part/bottom part/lid	lower part	Type	Bulkhead (feed-through)
Classifications			
ETIM 6.0	EC000437	ETIM 7.0	EC000437
ETIM 8.0	EC000437	ETIM 9.0	EC000437
ETIM 10.0	EC000437	ECLASS 9.0	27-44-02-02
ECLASS 9.1 ECLASS 11.0	27-44-02-02 27-44-02-02	ECLASS 10.0 ECLASS 12.0	27-44-02-02 27-44-02-02
ECLASS 11.0 ECLASS 13.0	27-44-02-02	ECLASS 12.0 ECLASS 14.0	27-44-02-02
ECLASS 15.0 ECLASS 15.0	27-44-02-02	ECLASS 14.0	27-44-02-02
Substance		Acetone	
Chemical resistance		Conditionally resistant	
Substance		Drilling oil	
Chemical resistance		Resistant	
Substance		Diesel	
Chemical resistance		Resistant	
Substance		Ethyl alcohol	
Chemical resistance		Resistant	
Substance		Transmission oil	

Creation date May 11, 2025 6:57:02 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Chemical resistance	Resistant	
Substance	Hydraulic oil	
Chemical resistance	Resistant	
Substance	Coolant	
Chemical resistance	Resistant	
Substance	Petroleum benzine	
Chemical resistance	Resistant	
Substance	Sweat	
Chemical resistance	Resistant	
Substance	Premium gasoline	
Chemical resistance	Conditionally resistant	
Substance	Water	
Chemical resistance	Resistant	
Substance	UV	
Chemical resistance	Unstable	
Substance	Ozone	
Chemical resistance	Unstable	

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	Potassium perfluorobutane sulfonate 29420-49-3
SCIP	e98b2b24-ba23-41bf-8d19-0dda3647412f
Chemical resistance	de.myview.objectmodel.impl.BlockImpl@e3f2e57 de.myview.objectmodel.impl.BlockImpl@64984655 de.myview.objectmodel.impl.BlockImpl@3ac312de de.myview.objectmodel.impl.BlockImpl@3ac312de de.myview.objectmodel.impl.BlockImpl@6cec98c2 de.myview.objectmodel.impl.BlockImpl@6bf59353 de.myview.objectmodel.impl.BlockImpl@6df59353 de.myview.objectmodel.impl.BlockImpl@63d73c67 de.myview.objectmodel.impl.BlockImpl@41208721 de.myview.objectmodel.impl.BlockImpl@5809eb9 de.myview.objectmodel.impl.BlockImpl@1ab22329 de.myview.objectmodel.impl.BlockImpl@1ab22329 de.myview.objectmodel.impl.BlockImpl@1ab22329

Important note

UL File Number Search

Certificate No. (cURus)

Product information	When mounting the housings, make sure that the flat gasket is correctly seated.

Approvals	
Approvals	
Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/
ROHS	Conform

UL Website E92202



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Con-	
formity	Manufacturer's declaration
Engineering Data	<u>CAD data – 1665860000 HDC 32A ABU STP.dxf</u>
	CAD data – STEP
Product Change Notification	20220214 Technical change to HDC housings
	20220214 Technische Änderung bei HDC-Gehäusen
Technical Documentation	<u>1665860000_HDC_32A_ABU_STP_Blatt1.pdf</u>
Catalogues	<u>Catalogues in PDF-format</u>
Brochures	<u>FL FIELDWIRING EN</u>
	<u>FL FIELDWIRING EN</u>



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A DODQ 4BO	Version
Order No.	<u>1665920000</u>	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190422950	condition), Cover for lower part of housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard

Hood, Cable Entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A TSBU 1M32G	Version
Order No.	<u>1787950000</u>	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205394	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 32
Туре	HDC 32A TSBU 1PG21G	Version
Type Order No.	HDC 32A TSBU 1PG21G 1665670000	Version HDC enclosures, Size: 7, Protection degree: IP65 (in plugged

Creation date May 11, 2025 6:57:02 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Туре	HDC 32A TSBU 1M25G	Version
Order No.	1787960000	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205400	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 25
Туре	HDC 32A TSBU 1PG29G	Version
Type Order No.	HDC 32A TSBU 1PG29G 1665690000	Version HDC enclosures, Size: 7, Protection degree: IP65 (in plugged

Hood, Cable Entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A TOBU 1PG21G	Version
Order No.	<u>1665790000</u>	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190422813	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 21
Туре	HDC 32A TOBU 1PG29G	Version
Order No.	<u>1665810000</u>	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190422837	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 29
Туре	HDC 32A TOBU 1M32G	Version
Order No.	<u>1787990000</u>	HDC enclosures, Size: 7, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205431	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 32