

## TS15X5 ST POK 0819

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Similar to illustration



Similar to illustration

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- Up to E60 fire rating dependent on the configuration
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

### General ordering data

|            |  |
|------------|--|
| Version    | Rail, TS 15, Width: 177 mm, without slot, Steel, galvanic zinc plated and passivated |
| Order No.  | <a href="#">8000003892</a>   |
| Type       | TS15X5 ST POK 0819   |
| GTIN (EAN) | 4050118652574  |
| Qty.       | 20 items   |

**Technical data**

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Dimensions and weights**

|            |         |                 |             |
|------------|---------|-----------------|-------------|
| Depth      | 5 mm    | Depth (inches)  | 0.1968 inch |
| Height     | 15 mm   | Height (inches) | 0.5906 inch |
| Width      | 177 mm  | Width (inches)  | 6.9685 inch |
| Net weight | 32.85 g |                 |             |

**Temperatures**

|                       |  |
|-----------------------|--|
| Operating temperature |  |
|-----------------------|--|

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**General information**

|                    |                                     |                  |              |
|--------------------|-------------------------------------|------------------|--------------|
| Material thickness | 1 mm                                | Standards        | DIN EN 60715 |
| Surface finish     | galvanic zinc plated and passivated | Basic material   | Steel        |
| Integral fixing    | Screwed                             | Stamp dimensions | 4.5 x 20 mm  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC001285    | ETIM 9.0    | EC001285    |
| ETIM 10.0   | EC001285    | ECLASS 14.0 | 27-40-06-02 |
| ECLASS 15.0 | 27-40-06-02 |             |             |