

RCH S21024**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Similar to illustration

General ordering data

Version	RIDERSERIES, Relay, Number of contacts: 2, CO contact AgNi, Rated control voltage: 24 V DC, Continuous current: 6 A, Screw connection, Test button available: No
Order No.	8768680000
Type	RCH S21024
GTIN (EAN)	4032248437474
Qty.	20 pc(s).

RCH S21024

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	25.5 mm	Depth (inches)	1.004 inch
Height	25.5 mm	Height (inches)	1.004 inch
Width	12.6 mm	Width (inches)	0.496 inch
Length	29 mm	Length (inches)	1.142 inch
Net weight	19.65 g		

Temperatures

Operating temperature	-25 °C...70 °C	Humidity	40 °C / 93 % rel. humidity, no condensation
-----------------------	----------------	----------	--

Rated data UL

Certificate No. (cURus)	E522350
-------------------------	---------

Control side

Rated control voltage	24 V DC	Rated current DC	29.2 mA
Power rating	700 mW	Status indicator	No

Load side

Rated switching voltage	250 V AC	Continuous current	6 A
Max. switching voltage, AC	250 V	AC switching capacity (resistive), max.	1500 VA
Switch-on delay	≤ 10 ms	Switch-off delay	≤ 4 ms
Contact type	2 CO contact (AgNi)	Mechanical service life	10 x 10 ⁶ switching cycles

General data

Test button available	No	Mechanical switch position indicator	No
Colour	Transparent		

Insulation coordination

Pollution severity	2	Surge voltage category	III
Creepage and clearance distance input – output	≥ 8 mm	Protection degree	IP20

Further details of approvals / standards

Standards	IEC 61810-1, UL508	Certificate No. (VDE)	40019897
Certificate No. (cURus)	E522350		

Connection data

Wire connection method	Screw connection	Pitch in mm (P)	5 mm
------------------------	------------------	-----------------	------

RCH S21024**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ETIM 9.0	EC001437
ETIM 10.0	EC001437	ECLASS 9.0	27-37-16-01
ECLASS 9.1	27-37-16-01	ECLASS 10.0	27-37-16-01
ECLASS 11.0	27-37-16-01	ECLASS 12.0	27-37-16-01
ECLASS 13.0	27-37-16-01	ECLASS 14.0	27-37-16-01
ECLASS 15.0	27-37-16-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Approvals

Approvals



Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319258/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319263/-T1z1mm-S800/
-----------------	---

ROHS	Conform
UL File Number Search	UL Website
Certificate No. (cURus)	E522350

Downloads

Catalogues	Catalogues in PDF-format
------------	--

RCH S21024

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Wiring diagram

Circuit diagram
View of connections

2 changeover contacts



1 NOC + 1 NCC

