

**KISC M3X15/6 SAK2.5 CU5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com



We offer a broad portfolio of mounting support for easy handling and supplementation of our products. From various tools to insulating sleeves and various screws, our components are matched to each other down to the last detail and thus facilitate assembly in compliance with the respective standards and protective regulations.

**General ordering data**

|            |                                   |
|------------|-----------------------------------|
| Version    | SAK Series, Mounting screw, Steel |
| Order No.  | <a href="#">0377200000</a>        |
| Type       | KISC M3X15/6 SAK2.5 CU5           |
| GTIN (EAN) | 4008 190006389                    |
| Qty.       | 100 items                         |

## KISC M3X15/6 SAK2.5 CU5

Weidmüller Interface GmbH & Co. KG  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com

## Technical data

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Dimensions and weights

|            |        |                 |             |
|------------|--------|-----------------|-------------|
| Depth      | 17 mm  | Depth (inches)  | 0.6693 inch |
| Height     | 4.8 mm | Height (inches) | 0.189 inch  |
| Width      | 4.8 mm | Width (inches)  | 0.189 inch  |
| Net weight | 1 g    |                 |             |

## Temperatures

|                     |                |                     |               |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Material data

|                |       |                |               |
|----------------|-------|----------------|---------------|
| Basic material | Steel | Surface finish | Miscellaneous |
| Colour         | grey  |                |               |

## System specifications

|         |             |
|---------|-------------|
| Version | for busbars |
|---------|-------------|

## Additional technical data

|                          |                 |                     |                 |
|--------------------------|-----------------|---------------------|-----------------|
| Type of fixing           | when screwed in | Installation advice | Direct mounting |
| Explosion-tested version | No              |                     |                 |

## Dimensions

|                                     |         |
|-------------------------------------|---------|
| Metric size of the thread, external | 3.00 mm |
|-------------------------------------|---------|

## General

|                     |                 |                |               |
|---------------------|-----------------|----------------|---------------|
| Installation advice | Direct mounting | Surface finish | Miscellaneous |
|---------------------|-----------------|----------------|---------------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 8.0    | EC002848    | ETIM 9.0    | EC002848    |
| ETIM 10.0   | EC002848    | ECLASS 14.0 | 27-25-03-90 |
| ECLASS 15.0 | 27-25-03-90 |             |             |