

# Product data sheet

## Characteristics

# LC1V610P7

Contactor, vacuum contactor LC1-V, 3P, 610A, AC-3, 220 to 240VAC coil



### Main

Range	TeSys
Product name	TeSys V
Product or component type	Vacuum contactor
Device short name	LC1V
Contactor application	Resistive load Motor control
Utilisation category	AC-3 AC-4 AC-1
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO

### Complementary

Coil technology	Without built-in bidirectional peak limiting diode suppressor
[Ie] rated operational current	610 A (at <55 °C) AC AC-3 for power circuit 630 A (at <40 °C) AC AC-1 for power circuit 540 A AC AC-4 for power circuit
Motor power kW	160 kW at 230 V AC 50/60 Hz (AC-3) 300 kW at 400 V AC 50/60 Hz (AC-3) 400 kW at 525 V AC 50/60 Hz (AC-3) 560 kW at 690 V AC 50/60 Hz (AC-3) 800 kW at 1000 V AC 50/60 Hz (AC-3)
Motor power hp	1000 Hp at 1000 V AC 50/60 Hz conforming to CSA 1300 Hp at 1500 V AC 50/60 Hz conforming to CSA 150 Hp at 200 V AC 50/60 Hz conforming to CSA 200 Hp at 240 V AC 50/60 Hz conforming to CSA 300 Hp at 380 V AC 50/60 Hz conforming to CSA 400 Hp at 480 V AC 50/60 Hz conforming to CSA 500 Hp at 600 V AC 50/60 Hz conforming to CSA 700 hp at 800 V AC 50/60 Hz conforming to CSA
Auxiliary contact composition	1 NO + 1 NC
[Uc] control circuit voltage	220...240 V AC 50/60 Hz
Control circuit voltage limits	0.8...1.1 Uc at 50/60 Hz
[Ui] rated insulation voltage	Power circuit: 1500 V Earth circuit: 2000 V Control circuit: 690 V
[Uimp] rated impulse withstand voltage	8 kV
Mounting support	Plate Rail
Connections - terminals	Control circuit: connector 1 x 2.5 mm <sup>2</sup> Power circuit: bolted connection
Tightening torque	Power circuit: 39 N.m - on connector - cable 185 mm <sup>2</sup> hexagonal screw head
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 50/60 Hz
[Ith] conventional free air thermal current	10 A for control circuit 630 A for power circuit
Irms rated making capacity	7300 A at 1500 V AC for power circuit conforming to IEC 60947
Rated breaking capacity	6100 A at 1500 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit 630 A aM at <= 1000 V for power circuit conforming to IEC 60947
Inrush power in VA	1700 VA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Hold-in power consumption in VA	28 VA
Operating time	24...32 ms on closing 95...115 ms on opening
Mechanical durability	2000000 cycles
Maximum operating rate	1200 cyc/h
Height	356 mm
Width	201 mm
Depth	178 mm
Net weight	13 kg

## Environment

Standards	EN 60947-4-1 IEC 60947-4-1
IP degree of protection	IP00 conforming to IEC 60529
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	3600...4500 m
Fire resistance	850 °C conforming to IEC 60695-2-1
Shock resistance	10 gn contactor closed 10 gn contactor opened
Vibration resistance	2 gn 10...500 Hz

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.54 cm
Package 1 Width	30.73 cm
Package 1 Length	50.8 cm
Package 1 Weight	15.56 kg
Unit Type of Package 2	S06
Number of Units in Package 2	2
Package 2 Height	73.5 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	42.4 kg

## Offer Sustainability

EU RoHS Directive	Not compliant
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------