

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings -your first choice for industrial housings with IP 65 protection.

Version	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged condition), Coupling housing, Side-
	locking clamp on lower side, Standard, Size of ca- ble entries: PG 21
	ble entries. FG 2 i
Order No.	<u>1657270000</u>
Туре	HDC 16B KBU 1PG21G
GTIN (EAN)	4008190410322
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

|--|

Height	64 mm	Height (inches)	2.52 inch
Width	55 mm	Width (inches)	2.165 inch
Net weight	286 g		

Temperatures

Limit temperature	-40 °C	125 °C

Dimensions

Cable entry	w. thread	Height of housing B	64 mm	
Total length housing	93.3 mm	Width housing C	43 mm	

General data

EMC housings	No	Housing main material	diecast aluminium
Material of locking element		Protection degree	IP65 (in plugged condi-
	Stainless steel, rust-proof		tion)
Surface finish	Powder coating		

Version

BG	6	Cable entry	w. thread
Clamp version	Side-locking clamp	Colour (RAL)	RAL 7035
Design	Standard	Design of housing	Coupling housing
Design of locking system	Side-locking clamp on low- er side	Internal thread	PG 21
Number of cable entry on top	1	Number of cable entry sideways	0
Sealing	NBR	Size	6
Size of cable entries	PG 21	Suitable for ModuPlug [®]	No
Top part/bottom part/lid	lower part	Туре	coupling extension

Classifications

Substance

EC000437	ETIM 7.0	EC000437	
EC000437	ETIM 9.0	EC000437	
EC000437	ECLASS 9.0	27-44-02-02	
27-44-02-02	ECLASS 10.0	27-44-02-02	
27-44-02-02	ECLASS 12.0	27-44-02-02	
27-44-02-02	ECLASS 14.0	27-44-02-02	
27-44-02-02			
	Acetone		
	Conditionally resista	nt	
	Drilling oil		
	Resistant		
	Diesel		
Chemical resistance		Resistant	
Substance			
Chemical resistance		Resistant	
	EC000437 EC000437 27-44-02-02 27-44-02-02 27-44-02-02	EC000437 EC000437 EC000437 ECLASS 9.0 ECLASS 10.0 ECLASS 12.0 ECLASS 14.0 ECLASS 14.0 ECLASS 14.0 ECLASS 14.0 ECLASS 15.0 ECLASS 14.0 ECLASS 15.0 ECLASS 16.0 ECLAS 16.0 ECLAS 16.0 ECLAS 16.0 ECLAS 16.0 ECLAS 16.0 ECLAS 16.	

Transmission oil

Creation date May 11, 2025 6:56:11 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Chemical resistance	Resistant	
Substance	Hydraulic oil	
Chemical resistance	Resistant	
Substance	Coolant	
Chemical resistance	Resistant	
Substance	Petroleum benzine	
Chemical resistance	Resistant	
Substance	Sweat	
Chemical resistance	Resistant	
Substance	Premium gasoline	
Chemical resistance	Conditionally resistant	
Substance	Water	
Chemical resistance	Resistant	
Substance	UV	
Chemical resistance	Unstable	
Substance	Ozone	
Chemical resistance	Unstable	

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption	
REACH SVHC	Potassium perfluorobutane sulfonate 29420-49-3	
SCIP	e98b2b24-ba23-41bf-8d19-0dda3647412f	
Chemical resistance	de.myview.objectmodel.impl.BlockImpl@7ccc5b91 de.myview.objectmodel.impl.BlockImpl@3b9be420 de.myview.objectmodel.impl.BlockImpl@4a28e9f1 de.myview.objectmodel.impl.BlockImpl@956a6c1 de.myview.objectmodel.impl.BlockImpl@73063886 de.myview.objectmodel.impl.BlockImpl@7a063886 de.myview.objectmodel.impl.BlockImpl@4230e1c4 de.myview.objectmodel.impl.BlockImpl@4e05a de.myview.objectmodel.impl.BlockImpl@5499605a de.myview.objectmodel.impl.BlockImpl@5499605a de.myview.objectmodel.impl.BlockImpl@612e347 de.myview.objectmodel.impl.BlockImpl@65510bb12	

Approvals

Approvals	(6. 13 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://
	mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/
ROHS	Conform
UL File Number Search	UL Website
Certificate No. (cURus)	E92202



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Co	on-
formity	Manufacturer's declaration
Engineering Data	CAD data – STEP
Product Change Notification	20220214 Technical change to HDC housings 20220214 Technische Änderung bei HDC-Gehäusen
Technical Documentation	1657270000_HDC_16B_KBU_1PG21G_STP_Blatt1.pdf
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN FL FIELDWIRING EN




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Hood, Cable Entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 16B TSBU 1M25G	Version
Order No.	<u>1788180000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205714	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 25
Туре	HDC 40D TSBU 1M25G	Version
Order No.	<u>1787010000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248204250	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 25
Туре	HDC 40D TSBU 1M40G	Version
Order No.	<u>1904800000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248521852	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 40
Туре	HDC 40D TSBU 1M32G	Version
Order No.	<u>1787000000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248204243	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 32
Туре	HDC 40D TSBU 1PG29G	Version
Order No.	<u>1656540000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409555	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 29
Туре	HDC 16B TSBU 1PG21G	Version
Order No.	<u>1656480000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409494	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 21
Туре	HDC 40D TSBU 1PG21G	Version
Order No.	<u>1656520000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409531	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 21
Туре	HDC 16B TSBU 1M40G	Version
Order No.	1809620000	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248284979	condition), Cable entry from side, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 40



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Hood, Cable Entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

-	LIDO AOD TODIL AMONO	v ·
Туре	HDC 40D TOBU 1M32G	Version
Order No.	<u>1787060000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248204304	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 32
Туре	HDC 40D TOBU 1PG29G	Version
Order No.	<u>1656650000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409661	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 29
Туре	HDC 16B TOBU 1PG21G	Version
Order No.	<u>1656590000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409609	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: PG 21
Туре	HDC 40D TOBU 2M25	Version
Order No.	1208380000	HDC enclosures, Size: 6, Protection degree: IP65, IP65 (in plugged
GTIN (EAN)	4032248100248	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 25
Туре	HDC 40D TOBU 1PG21G	Version
Order No.	<u>1656630000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190409647	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: PG 21
Туре	HDC 40D TOBU 1M25G	Version
Order No.	<u>1787070000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248204410	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, high, Size of cable entries: M 25
Туре	HDC 16B TOBU 1M25G	Version
Order No.	<u>1788210000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248205745	condition), Cable entry from top, Plug housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard, Size of cable entries: M 25



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 16B DODQ 4BO	Version
Order No.	<u>1665260000</u>	HDC enclosures, Size: 6, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190421960	condition), Cover for lower part of housing, Side-locking clamp on
Qty.	1 pc(s).	lower side, Standard