

**S-3L-320/10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

3-pole pin-type phase distribution bars are used for potential distribution to other components in the control cabinet such as circuit breakers, residual current circuit breakers and other installation devices.

**General ordering data**

|            |                                                                       |
|------------|-----------------------------------------------------------------------|
| Version    | Phase busbar (Terminals), 63, Number of poles: 18, Insulated: Yes, 10 |
| Order No.  | <a href="#">2658590000</a>                                            |
| Type       | S-3L-320/10                                                           |
| GTIN (EAN) | 4050118671933                                                         |
| Qty.       | 20 pc(s).                                                             |

**S-3L-320/10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |             |
|------------|---------|-----------------|-------------|
| Depth      | 15 mm   | Depth (inches)  | 0.591 inch  |
| Height     | 27.5 mm | Height (inches) | 1.083 inch  |
| Width      | 320 mm  | Width (inches)  | 12.598 inch |
| Net weight | 32.35 g |                 |             |

**Temperatures**

|                     |               |
|---------------------|---------------|
| Ambient temperature | -5 °C...40 °C |
|---------------------|---------------|

**Material data**

|        |      |
|--------|------|
| Colour | grey |
|--------|------|

**Additional technical data**

|                          |    |
|--------------------------|----|
| Explosion-tested version | No |
|--------------------------|----|

**Dimensions**

|                 |         |
|-----------------|---------|
| Pitch in mm (P) | 17.8 mm |
|-----------------|---------|

**General**

|                 |    |
|-----------------|----|
| Number of poles | 18 |
|-----------------|----|

**Rating data**

|                     |                    |               |       |
|---------------------|--------------------|---------------|-------|
| Rated cross-section | 10 mm <sup>2</sup> | Rated voltage | 400 V |
| Rated current       | 63 A               |               |       |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 7.0    | EC000215    | ETIM 8.0    | EC000215    |
| ETIM 9.0    | EC000215    | ETIM 10.0   | EC000215    |
| ECLASS 11.0 | 27-37-13-06 | ECLASS 12.0 | 27-37-13-06 |
| ECLASS 13.0 | 27-37-13-06 | ECLASS 14.0 | 27-37-13-06 |
| ECLASS 15.0 | 27-37-13-06 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

Approvals



|                 |                                                                                                                                                                             |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> |
| ROHS            | Conform                                                                                                                                                                     |

### S-3L-320/10

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of Con-  
formity

[CE Declaration of Conformity](#)

Engineering Data

[CAD data – STEP](#)

Catalogues

[Catalogues in PDF-format](#)

## S-3L-320/10

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Drawing

