

## VPU AC I 4 R 275/25 LCF S

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany


[www.weidmueller.com](http://www.weidmueller.com)

### Product image



Abb.ähnlich

Weidmüller VPU I (Type I), VPU II (Type II) and VPU III (Type III) surge protection products effectively reduce the interference coupling that can occur due to transient surge voltages, even significantly below the limits prescribed by insulation co-ordination according to EN 60664-3 / DIN VDE 0110-3. This means that the whole installation is exposed to fewer malfunctions. The arresters are co-ordinated using technical means. This means that decoupling between Types I, II and III is unnecessary. The arresters are tested according to product standard IEC 61643-11 / DIN EN 61643-11 and can be installed in systems according to IEC 61643-12 / VDE 0675-6-12 and IEC 62305-4 / VDE 0185-4. This lightning and surge protection device is suited for installation in power supply systems. Weidmüller offers different products depending on the particular mains network type and voltage level. A special Type I and Type II protective device is even available for photovoltaic applications.



### General ordering data

|                   |                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------|
| Version           | Surge voltage arrester, Low voltage, Surge protection, Leakage-current-free, with remote contact, TN-C-S, TN-S |
| Order No.         | <a href="#">2726790000</a>                                                                                     |
| Type              | VPU AC I 4 R 275/25 LCF S                                                                                      |
| GTIN (EAN)        | 4050118802498                                                                                                  |
| Qty.              | 1 pc(s).                                                                                                       |
| Replacement parts | <a href="#">2730860000</a> <a href="#">2855300000</a>                                                          |

## VPU AC I 4 R 275/25 LCF S

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 91 mm    | Depth (inches)  | 3.583 inch |
| Height     | 104.5 mm | Height (inches) | 4.114 inch |
| Width      | 72 mm    | Width (inches)  | 2.835 inch |
| Net weight | 676 g    |                 |            |

## Temperatures

|                     |                       |                       |                |
|---------------------|-----------------------|-----------------------|----------------|
| Storage temperature | -40 °C...85 °C        | Operating temperature | -40 °C...85 °C |
| Humidity            | 5 - 95% rel. humidity |                       |                |

## Connection data, remote alert

|                                                    |                      |                                                    |                     |
|----------------------------------------------------|----------------------|----------------------------------------------------|---------------------|
| Connection type                                    | PUSH IN              | Cross-section for connected wire, solid core, max. | 1.5 mm <sup>2</sup> |
| Cross-section for connected wire, solid core, min. | 0.14 mm <sup>2</sup> | Stripping length                                   | 8 mm                |

## General data

|                 |               |                   |                         |
|-----------------|---------------|-------------------|-------------------------|
| Number of poles | 4             | Protection degree | IP20 in installed state |
| Colour          | orange, black |                   |                         |

## Insulation coordination acc. to EN 50178

|                    |   |                        |    |
|--------------------|---|------------------------|----|
| Pollution severity | 2 | Surge voltage category | IV |
|--------------------|---|------------------------|----|

## Rated data IEC / EN

|                                               |                             |                                                            |                                                                      |
|-----------------------------------------------|-----------------------------|------------------------------------------------------------|----------------------------------------------------------------------|
| Discharge current $I_{\max}$ (8/20μs) wire-PE | 65 kA                       | Discharge current $I_n$ (8/20μs) wire-PE                   | 25 kA                                                                |
| Energy coordination (≤10 m)                   | Type I, Type II, Type III   | Follow-on current extinguishing capability $I_{fi}$        | 50 kA                                                                |
| Frequency range, max.                         | 60 Hz                       | Frequency range, min.                                      | 50 Hz                                                                |
| Fuse                                          | No Fuse necessary ≤315 A gL | Integrated back-up fuse                                    | No                                                                   |
| Leakage current at $U_n$                      | 1 μA                        | Lightning test current $I_{\text{imp}}$ (10/350 μs) (L-PE) | 25 kA                                                                |
| Low voltage network                           | TN-C-S, TN-S                | Mains voltage                                              | 230 V / 400 V                                                        |
| Max. continuous voltage, $U_c$ (AC)           | 275 V                       | Note follow current capability                             | No tripping of a 16 A gG fuse up to prospective 50 kA <sub>eff</sub> |
| Number of poles                               | 4                           | PE conductor current $I_{PE}$                              | 1 μA                                                                 |
| Protection level $U_p$ at $I_N$ (L/N-PE)      | ≤ 1.5 kV                    | Rated voltage (AC)                                         | 230 V                                                                |
| Requirements category acc. to IEC 61643-11    | Type I, Type II             | Requirements class, acc. to EN 61643-11                    | T1, T2                                                               |
| Response time                                 | <100 ns                     | Short-circuit current rating $I_{SCCR}$                    | 50 kA                                                                |
| Signalling contact                            | 250 V 1A 1CO                | Standards                                                  | IEC 61643-11, EN 61643-11                                            |
| Temporary surge voltage (over-voltage) - TOV  | 442 V                       | Voltage type                                               | AC                                                                   |

## VPU AC I 4 R 275/25 LCF S

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Connection data

|                                                            |                    |                                                            |                     |
|------------------------------------------------------------|--------------------|------------------------------------------------------------|---------------------|
| Stripping length                                           | 18 mm              | Wire connection method                                     | Screw connection    |
| Type of connection                                         | Screw connection   | Stripping length, rated connection                         | 18 mm               |
| Tightening torque, min.                                    | 3 Nm               | Tightening torque, max.                                    | 4.5 Nm              |
| Clamping range, rated connection                           | 16 mm <sup>2</sup> | Clamping range, min.                                       | 1.5 mm <sup>2</sup> |
| Clamping range, max.                                       | 35 mm <sup>2</sup> | Wire cross-section, solid, min.                            | 2.5 mm <sup>2</sup> |
| Wire cross-section, solid, max.                            | 35 mm <sup>2</sup> | Wire connection cross section, finely stranded, min.       | 2.5 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, max.       | 35 mm <sup>2</sup> | Conductor cross-section, flexible, AEH (DIN 46228-1), min. | 2.5 mm <sup>2</sup> |
| Conductor cross-section, flexible, AEH (DIN 46228-1), max. | 35 mm <sup>2</sup> | Connection cross-section, stranded, min.                   | 2.5 mm <sup>2</sup> |
| Connection cross-section, stranded, max.                   | 35 mm <sup>2</sup> |                                                            |                     |

## Electrical data

|              |    |
|--------------|----|
| Voltage type | AC |
|--------------|----|

## Guarantee

|               |         |
|---------------|---------|
| Time interval | 5 years |
|---------------|---------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000941    | ETIM 7.0    | EC000941    |
| ETIM 8.0    | EC000941    | ETIM 9.0    | EC000941    |
| ETIM 10.0   | EC000941    | ECLASS 9.0  | 27-13-08-05 |
| ECLASS 9.1  | 27-13-08-05 | ECLASS 10.0 | 27-13-08-05 |
| ECLASS 11.0 | 27-13-08-05 | ECLASS 12.0 | 27-17-90-90 |
| ECLASS 13.0 | 27-17-90-90 | ECLASS 14.0 | 27-17-90-90 |
| ECLASS 15.0 | 27-17-90-90 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Important note

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Product information | For use in DC applications, please use the fuse of SIBA Type NH2XL aR/aSF DC 1500 V |
|---------------------|-------------------------------------------------------------------------------------|

## Approvals

Approvals



|                 |                                                                                                                                                                                                                                                                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319263/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319263/-T1z1mm-S800/</a> |
| ROHS            | Conform                                                                                                                                                                                                                                                                                                                                                 |

### VPU AC I 4 R 275/25 LCF S

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of Conformity

[EU\\_Konformitätserklärung / EU\\_Declaration\\_of\\_Conformity](#)

Engineering Data

[CAD data – STEP](#)

Tender specification

[Ausschreibungstext DE](#)

[Tenderspecification EN](#)

User Documentation

[Beipackzettel / Instruction sheet](#)

Catalogues

[Catalogues in PDF-format](#)

## VPU AC I 4 R 275/25 LCF S

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26


D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Electric symbol




Schematic circuit diagram

**VPU AC I 4 R 275/25 LCF S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Slotted screwdriver**

VDE insulated slot-head screwdriver, SDI DIN 7437, ISO 2380/2, drive output acc. to DIN 5264, ISO 2380/1. SoftFinish grip

**General ordering data**

|            |                            |                                                                   |
|------------|----------------------------|-------------------------------------------------------------------|
| Type       | SDIS 1.0X5.5X125           | Version                                                           |
| Order No.  | <a href="#">2749850000</a> | Screwdriver, Blade width (B): 5.5 mm, Blade length: 125 mm, Blade |
| GTIN (EAN) | 4050118897050              | thickness (A): 1 mm                                               |
| Qty.       | 1 pc(s).                   |                                                                   |

**Crosshead screwdriver Phillips**

VDE insulated crosshead screwdriver, for Phillips screws, SDIK PH DIN 7438, ISO 8764/2-PH, output to ISO 8764-PH, SoftFinish grip

**General ordering data**

|            |                            |                                                                   |
|------------|----------------------------|-------------------------------------------------------------------|
| Type       | SDIK PH1 X 80              | Version                                                           |
| Order No.  | <a href="#">2749890000</a> | Screwdriver, Blade width (B): 1 mm, 80 mm, Blade thickness (A): 1 |
| GTIN (EAN) | 4050118897098              |                                                                   |
| Qty.       | 1 pc(s).                   |                                                                   |

**VPU AC I 4 R 275/25 LCF S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Blank**

ESG is the tried-and-tested marker in MultiCard format for use on many well-known electrical devices. The result is high-quality device marking with a high-contrast appearance.

Various types are available for devices from manufacturers like Siemens, ABB, Beckhoff etc.

Advantages at a glance:

- Tags for universal usage, self-adhesive or clip-on tags, depending on type
- For aligned equipment, e.g. circuit breakers, we supply ESG markers for clipping onto tag rails
- Individual laser-quality printing according to specifications

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|            |                            |                                                                  |
|------------|----------------------------|------------------------------------------------------------------|
| Type       | ESG 6/15 K MC NE WS        | Version                                                          |
| Order No.  | <a href="#">1880100000</a> | ESG, Device markers x 15 mm, PA 66, Colour: white, Self-adhesive |
| GTIN (EAN) | 4032248478781              |                                                                  |
| Qty.       | 200 pc(s).                 |                                                                  |

**VPU AC I 4 R 275/25 LCF S****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Replacement parts****VPU Series**

Extensive accessories round off the product range

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | PLUG VPU AC                |
| Order No.  | <a href="#">2855300000</a> |
| GTIN (EAN) | 4064675533283              |
| Qty.       | 10 pc(s).                  |

**Spare arrester**

In the event of a defective arrester, you can easily reorder this spare arrester, replace the defective arrester and thus restore protection.

**General ordering data**

|            |                            |                                                        |
|------------|----------------------------|--------------------------------------------------------|
| Type       | VPU AC I O 275/25 LCF S    | Version                                                |
| Order No.  | <a href="#">2730860000</a> | Spare arrester, Leakage-current-free, Surge protection |
| GTIN (EAN) | 4050118808025              |                                                        |
| Qty.       | 1 pc(s).                   |                                                        |