
NEOZED® fuse enclosure

# GSN 5210-400 Plus



## GSN 5210-400 Plus

**NEOZED® fuse enclosure**

CUSTOMIZABLE

Productnumber: 05551084
Dimensions: 640 x 440 x 179 mm

NEOZED® fuse enclosure with additional connection space, 10 x 3-pole D02 bus-mounting fuse base, E 18 thread, Rated current 63 A, Screw connection 1.5 - 25 mm², on 5-pole busbar, with 5 busbar terminals 16 - 70 mm², N terminal 1.5 - 16 mm², PE terminal 1.5 - 16 mm², 4 x enclosure connectors (GGV)

**on busbar system 400 A, with transparent cover**

IP65 IK08 690V AC 1000V DC

# Technical Data

## electrical characteristics

| | |
|---|---|
| Rated insulation voltage AC: | 690 V |
| Rated insulation voltage DC: | 1000 V |
| Protection class: | II |
| Type of protection: | IP65 |
| UL Type Rating: | 3R |

## Dimensions

| | |
|---|---|
| Width: | 640 mm |
| Length: | 440 mm |
| Height: | 179 mm |
| Weight: | 12.295 kg |

## Material characteristics

| | |
|---|---|
| UV-resistant: | yes |
| Halogen free: | yes |
| Glow-wire flammability: | 960 °C (EN 60695-2-11) |

## mechanical properties

| | |
|---|---|
| Impact strength: | IK08 |
| Cover screw torque: | 2.5 Nm |
| Stackable: | yes |

## Ambient conditions

| | |
|---|---|
| max. relative humidity 25°C: | 95 % |
| max. relative humidity 40°C: | 50 % |
| Min. ambient temperature: | -25 °C |
| Max. ambient temperature: | 40 °C |
| 24h ambient temperature: | 35 °C |
| Installation location: | protected outdoor areas |

## Sales Information

| | |
|---|---|
| EAN: | 4013902988389 |
| ETIM Class: | EC000100 |
| Custom tariff number: | 85369095 |
| Minimum order quantity: | 1 |

## Material

| | |
|---|---|
| Base unit material: | Polycarbonate |
| Cover material: | Polycarbonate, glass-fibre reinforced |
| Sealing material: | Polyurethane |
| Cover screw material: | Polyamide, glass-fibre reinforced |

Created at 04.06.2026. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299