

Product image

The distribution or multiplication of a potential to adjoining terminal blocks is realized via a cross-connection. Additional wiring effort can be easily avoided. Even if the poles are broken out, contact reliability in the terminal blocks is still ensured. Our portfolio offers pluggable and screwable cross-connection systems for modular terminal blocks.

General ordering data

| | |
|------------|---|
| Version | Connecting sleeve (terminal), when screwed in, Width: 6 mm, Height: 6 mm, Depth: 19 mm, Number of poles: 1, Cu Zn |
| Order No. | 0318000000 |
| Type | VH 19/6.3/4.3 |
| GTIN (EAN) | 4008190059460 |
| Qty. | 50 items |

Technical data

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Dimensions and weights

| | | | |
|----------|-------|-----------------|-------------|
| Depth | 19 mm | Depth (inches) | 0.748 inch |
| Height | 6 mm | Height (inches) | 0.2362 inch |
| Width | 6 mm | Width (inches) | 0.2362 inch |
| Diameter | 6 mm | Net weight | 2.77 g |

Temperatures

| | | | |
|---------------------|----------------|---------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
|---------------------|----------------|---------------------|---------------|

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | 73c55621-8329-401d-bde2-7fd78e0e60e4 |

Material data

| | | | |
|----------------|-------|--------|------|
| Basic material | Cu Zn | Colour | grey |
|----------------|-------|--------|------|

System specifications

| | |
|---------|---------------------------|
| Version | for cross-connection link |
|---------|---------------------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Type of fixing | when screwed in | Installation advice | Direct mounting |
| Explosion-tested version | No | | |

Dimensions

| | |
|----------|------|
| Diameter | 6 mm |
|----------|------|

General

| | | | |
|-----------------|---|---------------------|-----------------|
| Number of poles | 1 | Installation advice | Direct mounting |
|-----------------|---|---------------------|-----------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC002848 | ETIM 9.0 | EC002848 |
| ETIM 10.0 | EC002848 | ECLASS 14.0 | 27-25-03-90 |
| ECLASS 15.0 | 27-25-03-90 | | |