

**LM WO 25.4/57 GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

Similar to illustration

Self-adhesive polyester labels which are suitable for A4 office laser printer.

**General ordering data**

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| Version    | LaserMark, Conductor and cable markers, 6.8 - 12 mm, 25.4 x 57 mm, yellow |
| Order No.  | <a href="#">1768390000</a>                                                |
| Type       | LM WO 25.4/57 GE                                                          |
| GTIN (EAN) | 4032248110032                                                             |
| Qty.       | 10 pc(s).                                                                 |

## LM WO 25.4/57 GE

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 0.025 mm | Depth (inches)  | 0.001 inch |
| Height     | 25.4 mm  | Height (inches) | 1 inch     |
| Width      | 57 mm    | Width (inches)  | 2.244 inch |
| Net weight | 10.1 g   |                 |            |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...150 °C |
|-----------------------------|--------------|

## General data

|                                              |                                                |             |
|----------------------------------------------|------------------------------------------------|-------------|
| Adhesive                                     | Acrylate                                       |             |
| Colour                                       | yellow                                         |             |
| Halogen                                      | No                                             |             |
| Material                                     | Polyester film                                 |             |
| Material colour according to resistance code | 4                                              |             |
| Number of markers per combination            | 1 Label sheet = 35 Conductor and cable markers |             |
| Number of markers per packaging unit         | 350                                            |             |
| Number of markers per packaging unit         | Number of markers per combination              | 35          |
|                                              | Form of supply                                 | Label sheet |
|                                              | Number of combinations per packaging unit      | 10          |
| Number per sheet                             | 35                                             |             |
| Operating temperature range                  | -40...150 °C                                   |             |
| Operating temperature range, max.            | 150 °C                                         |             |
| Operating temperature range, min.            | -40 °C                                         |             |
| Size of labelling field                      | 25.4 x 18 mm                                   |             |
| Type of printing                             | neutral                                        |             |
| UL 94 flammability rating                    | V-0                                            |             |
| Version                                      | Self-adhesive                                  |             |
| Width                                        | 57 mm                                          |             |

## Conductor and cable markers

|                               |                    |                                  |                         |
|-------------------------------|--------------------|----------------------------------|-------------------------|
| Conductor O.D.                | 6.8 - 12 mm        | Conductor O.D., max.             | 12 mm                   |
| Conductor O.D., min.          | 6.8 mm             | Conductor cross-section, max.    | 50 mm <sup>2</sup>      |
| Conductor cross-section, min. | 10 mm <sup>2</sup> | Cross-section for connected wire | 10 - 50 mm <sup>2</sup> |
| Halogen                       | No                 | Text field height                | 18.5 mm                 |
| Text field width              | 25.4 mm            |                                  |                         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ETIM 8.0    | EC001530    | ETIM 9.0    | EC001530    |
| ETIM 10.0   | EC001530    | ECLASS 9.0  | 27-40-04-01 |
| ECLASS 9.1  | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 | ECLASS 12.0 | 27-28-11-02 |
| ECLASS 13.0 | 27-28-11-02 | ECLASS 14.0 | 27-28-11-02 |
| ECLASS 15.0 | 27-28-11-02 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

Creation date May 11, 2025 7:12:46 PM CEST

## LM WO 25.4/57 GE

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Approvals

ROHS

Conform

### Downloads

Engineering Data

[CAD data – STEP](#)

Catalogues

[Catalogues in PDF-format](#)

**LM WO 25.4/57 GE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

