



Hoofd

Product or component type	Hulpcontact
Bereik compatibiliteit	Compact Compact NS630b...1600
Samenstelling signaleringscontacten	1 NO/NC

Complementair

Type hulpcontacten	Standaard
Werking hulpcontacten	Early-make
Mounting mode	Clip-on
Ith conventionele thermische stroom in vrije lucht	6 A
Onderbrekingsvermogen (A)	AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 6 A at 24 V AC 50/60 Hz AC-15: 6 A at 48 V AC 50/60 Hz AC-15: 5 A at 110 V AC 50/60 Hz AC-15: 4 A at 220/240 V AC 50/60 Hz AC-15: 2 A at 380/440 V AC 50/60 Hz AC-15: 1,5 A at 480 V AC 50/60 Hz AC-15: 0,1 A at 660/690 V AC 50/60 Hz DC-12: 6 A at 24 V DC 50/60 Hz DC-12: 2,5 A at 48 V DC 50/60 Hz DC-12: 0,6 A at 110 V DC 50/60 Hz DC-12: 0,3 A at 250 V DC 50/60 Hz DC-14: 1 A at 24 V DC DC-14: 0,2 A at 48 V DC DC-14: 0,05 A at 110 V DC DC-14: 0,03 A at 250 V DC
Minimale belasting	100 mA bij 24 V DC

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5,0 cm
Package 1 Width	11,0 cm
Package 1 Length	18,0 cm
Package 1 Weight	60,0 g

Duurzaamheid van het aanbod

REACH-regelgeving	 REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet  EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.
PVC-vrij	Ja

contractuele waarborg

Garantie	18 months
----------	-----------