



Hoofd

Range	ComPacT
Range of product	Compact nsx100...250 Compact nsx100...250 nieuwe generatie Compact nsx400...630 Compact nsx400...630 nieuwe generatie Compact nsx100...250 DC Compact nsx100...250 DC nieuwe generatie Compact nsx100...250 DC PV Compact nsx100...250 DC PV nieuwe generatie Compact nsx400...630 DC Compact nsx400...630 DC nieuwe generatie Compact nsx400...630 DC PV Compact nsx400...630 DC PV nieuwe generatie
Device short name	MN
Product or component type	Spanningslosser
Device application	Controle
Type uitschakeling spanning	Starter Vrijgave onderspanning
Spanning stuurkring	380...415 V AC 50 Hz 440...480 V AC 60 Hz
Bereik compatibiliteit	ComPacT nieuwe generatie Compact nsx nieuwe generatie ComPacT nieuwe generatie Compact nsx DC nieuwe generatie Compact Compact NSX Compact COMPACT NSX DC EasyPact EasyPact CVS PowerPact PowerPact multi-standaard

Complementair

Operationele grens	0,35...0,7 x Un opening 0,85 x Un sluiting
Responstijd	50 ms
Voeding houdvermogen	5 VA
Voeding inschakelstroom	10 VA
Hulpaansluitklem	Veer 0,5...1,5 mm ² (AWG 20...AWG 16)
Wire stripping length	7 mm

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,400 cm
Package 1 Width	4,700 cm
Package 1 Length	6,200 cm
Package 1 Weight	112,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7,100 cm
Package 2 Width	10,500 cm
Package 2 Length	23,600 cm
Package 2 Weight	1,850 kg

Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30,000 cm
Package 3 Width	30,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	7,510 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
EU-richtlijn RoHS	Voldoet aan vrijstellingen
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product
Circulair Profiel	Geen specifieke recycling vereist
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.
PVC-vrij	Ja

contractuele waarborg

Garantie	18 months
----------	-----------