

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings -your first choice for industrial housings with IP 65 protection.

Version	HDC enclosures, Size: 5, Protection degree: IP65
	(in plugged condition), Cable entry from top, Plug
	housing, End-locking clamp, lower side, Standard,
	Size of cable entries: PG 16
Order No.	<u>1664810000</u>
Туре	HDC 16A TOLU 1PG16G
GTIN (EAN)	4008190421519
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Dim	ensions	and	weights
PIIII	GHOIDHO	anu	weights

Dimensions and weights			
D	00	D (1 (1 )	0.504: 1
Depth	89 mm 58 mm	Depth (inches)	3.504 inch
Height Width	32.5 mm	Height (inches) Width (inches)	2.283 inch 1.28 inch
Net weight	124 g	width (inches)	1.20 IIICII
<u> </u>	12.19		
Temperatures			
Limit temperature	-40 °C 125 °C		
Dimensions			
Cable entry	w. thread	Height of housing B	58 mm
Total length housing	79 mm	Width housing C	29.5 mm
General data	70 111111	Width Hodoling O	20.0 11111
General data			
EMC housings	No	Housing main material	diecast aluminium
Material of locking element		Protection degree	IP65 (in plugged condi-
	Stainless steel, rust-proof	· -	tion)
Surface finish	Powder coating	Tightening torque	0.5 Nm
Version			
BG	5	Cable entry	w. thread
Clamp version	End-locking clamp	Colour (RAL)	RAL 7035
Design	Standard	Design of housing	Cable entry from top, Plug
Design of locking system	End-locking clamp, lower side	Internal thread	PG 16
Number of cable entry on top	1	Number of cable entry sideways	0
Sealing	NBR	Size	5
Size of cable entries	PG 16	Suitable for ModuPlug <sup>®</sup>	No
Tightening torque	0.5 Nm	Top part/bottom part/lid	upper part
Туре	Plug		
Classifications			
ETIM 6.0	EC000437	ETIM 7.0	EC000437
ETIM 8.0	EC000437	ETIM 9.0	EC000437
ETIM 10.0	EC000437	ECLASS 9.0	27-44-02-02
ECLASS 9.1	27-44-02-02	ECLASS 10.0	27-44-02-02
ECLASS 11.0	27-44-02-02	ECLASS 12.0	27-44-02-02
ECLASS 13.0	27-44-02-02	ECLASS 14.0	27-44-02-02
ECLASS 15.0	27-44-02-02		
Substance		Acetone	
Chemical resistance		Conditionally resistant	
Substance		Drilling oil	
Chemical resistance		Resistant	
Substance		Diesel	
Chemical resistance		Resistant	
Substance		Ethyl alcohol	

Creation date May 11, 2025 6:56:46 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

Chemical resistance	Resistant	
Substance	Transmission oil	
Chemical resistance	Resistant	
Substance	Hydraulic oil	
Chemical resistance	Resistant	
Substance	Coolant	
Chemical resistance	Resistant	
Substance	Petroleum benzine	
Chemical resistance	Resistant	
Substance	Sweat	
Chemical resistance	Resistant	
Substance	Premium gasoline	
Chemical resistance	Conditionally resistant	
Substance	Water	
Chemical resistance	Resistant	
Substance	UV	
Chemical resistance	Unstable	
Substance	Ozone	
Chemical resistance	Unstable	

### **Environmental Product Compliance**

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%
Chemical resistance	de.myview.objectmodel.impl.BlockImpl@c686c3 de.myview.objectmodel.impl.BlockImpl@2eed1e96 de.myview.objectmodel.impl.BlockImpl@5e727e59 de.myview.objectmodel.impl.BlockImpl@5e727e59 de.myview.objectmodel.impl.BlockImpl@6e3b60bca de.myview.objectmodel.impl.BlockImpl@2ce9a1a4 de.myview.objectmodel.impl.BlockImpl@100703d8 de.myview.objectmodel.impl.BlockImpl@5dca2737 de.myview.objectmodel.impl.BlockImpl@667dfad5 de.myview.objectmodel.impl.BlockImpl@667dfad5 de.myview.objectmodel.impl.BlockImpl@42b35970 de.myview.objectmodel.impl.BlockImpl@42b35970

### **Approvals**

Approvals	(Eg Sus
Approvals MAMID	https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/ https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/
ROHS	Conform
UL File Number Search	UL Website
Certificate No. (cURus)	E92202



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

#### **Downloads**

Approval/Certificate/Document of Con	-
formity	Manufacturer's declaration
Engineering Data	CAD data – STEP
Product Change Notification	20220214 Technical change to HDC housings 20220214 Technische Änderung bei HDC-Gehäusen
Technical Documentation	1664810000_HDC_16A_TOLU_1PG16G_STP_Blatt1.pdf
Catalogues	Catalogues in PDF-format
Brochures	FL FIELDWIRING EN FL FIELDWIRING EN




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Drawings**





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Base housing**



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

	oraoring aata	
Туре	HDC 16A SLU 2PG16G	Version
Order No.	<u>1665070000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190421779	condition), Base housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: PG 16
Туре	HDC 16A SLU 1M25G	Version
Order No.	1902330000	HDC enclosures, Size: 5, Protection degree: IP65, IP65 (in plugged
GTIN (EAN)	4032248591916	condition), Base housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: M 25
Туре	HDC 16A SLU 2M25G	Version
Order No.	<u>1788760000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248206308	condition), Base housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: M 25
Туре	HDC 16A SLU 1PG21G	Version
Order No.	<u>1665090000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190421793	condition), Base housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: PG 21
Туре	HDC 16A SLU 2M20G	Version
Order No.	<u>1788770000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248206315	condition), Base housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: M 20



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Bulkhead housing**



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

### **General ordering data**

Туре	HDC 16A ALU	Version
Order No.	<u>1664920000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190421625	condition), Bulkhead housing, End-locking clamp, lower side, Standard
Qty.	1 pc(s).	

### Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 16A DODL 1LB	Version
Order No.	<u>1665900000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4008190422936	condition), Cover for lower part of housing, End-locking clamp, lower
Qty.	1 pc(s).	side, Standard



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Accessories**

#### **Coupling housing**



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

Туре	HDC 16A KLU 1M25G	Version
Order No.	<u>1788800000</u>	HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
GTIN (EAN)	4032248206346	condition), Coupling housing, End-locking clamp, lower side, Standard,
Qty.	1 pc(s).	Size of cable entries: M 25
Туре	HDC 16A KLU 1PG16G	Version
Type Order No.	HDC 16A KLU 1PG16G 1665450000	Version HDC enclosures, Size: 5, Protection degree: IP65 (in plugged
• •		