

Data sheet

Page 2/6

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 jack straight - free line end, drag chain, PUR

P/N

142M1D20010

EAN 4251394624488

2026/09/29

Version: L

Technical Data

General Data	
Fields of application	Industrial Ethernet
Design	Ethernet-Connection line
Cable length (m)	1 m
Cable length (ft)	3.28 ft
Cable	
Cable Type	SF/FTP
Wiring	Profinet
Wire color	yellow, white, orange, blue
Color - cable jacket	green
Transmission properties	5e
Connection 1	
Shielding	shielded
Dimension (L x W x H)	52 mm x 21.5 mm x 21.5 mm
Dimension (L x W x H)	2.047 in. x 0.846 in. x 0.846 in.

Connections/interfaces	
Cable	
Conductor cross section AWG	AWG 22/7
Conductor diameter (mm)	0.75 mm
Conductor diameter (inch)	0.03 in.
Outer diameter cable jacket (mm)	6.5 mm
Outer diameter cable jacket (inch)	0.256 in.
Connection 1	
Connector type	M12-jack
Coding	D-coded
Type of plug contact, field side	Female (bus)
Cable feed arrangement, field side	straight
Number of poles	4
Pin Assignment	1 YE, 2 WH, 3 OG, 4 BU
Latching lever protection	no
Color of the cable boot	black



Data sheet

Page 3/6

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 jack straight - free line end, drag chain, PUR

P/N

142M1D20010

EAN 4251394624488

2026/09/29

Version: L

Technical Data

Electrical characteristics

Connection 1

Current carrying capacity per pin (at 40 °C)	4 A
--	-----

Mechanical data

Cable

drag chain suitable	yes
Bending radius (fixed)	26 mm
Bending radius (moved)	52 mm
Number of alternating bending cycles (mechanical resistance) at:	3 million bending cycles
Alternating bending radius	100 mm
velocity	4 m/s
acceleration	4 m/s ²

Connection 1

Mechanical life	min. 100 mating cycles
-----------------	------------------------

Materials and material properties

Cable

Material - Cable jacket	PUR
Material - Wire insulation	FRNC
Flame retardancy	yes, according to IEC 60332-1-2

Connection 1

Material - Contact	CuZnPb (brass)
Material - Contact surface	Au (gold)
Material - Contact carrier	Plastics, PA, BK
Material - Body	Plastics, TPU, BK
Material - Flange housings	Metal, CuZn, nickel-plated
Material - Sealing (jack)	FPM/FKM
Material - Outer sealing	NBR

Data sheet

Page 4/6

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 jack straight - free line end, drag chain, PUR

P/N

142M1D20010

EAN 4251394624488

2026/09/29

Version: L

Technical Data

Environmental conditions	
Cable	
Temperature range (fixed)	-30 °C - max. 70 °C
Temperature range (fixed)	-22 °F - 158 °F
Connection 1	
	-40 °C
	-40 °F
Protection category (mounted)	IP67 (-30 °C...+90 °C), IP65 (-40 °C...+90 °C)
Standards/Regulations	
Profinet	Type C
Classifications	
ETIM 9.0	EC002599
ETIM 10.0	EC002599
Packing details	
Type of packaging	1 pc(s) / plastic bag

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

Data sheet

Page 5/6

**M12 Industrial Ethernet cable, D-coded, 1.0 m,
M12 jack straight - free line end, drag chain, PUR**

P/N

142M1D20010


EAN 4251394624488

2026/09/29


Version: L

Illustrations

Dimensional drawing



Cut-out



Data sheet

Page 6/6

**M12 Industrial Ethernet cable, D-coded, 1.0 m,
M12 jack straight - free line end, drag chain, PUR**

P/N

142M1D20010


EAN 4251394624488

2026/09/29

Version: L

Illustrations

Wiring diagram



Principle diagram

