LVS04121

Busbar, Linergy BW, 4P, 160A, insulated busbar, vertical, L1000mm





Main Linergy Range Linergy Range of product Product or component Busbar type Product name Linergy BW PrismaSeT PrismaSeT G enclosure Range compatibility PrismaSeT PrismaSeT P enclosure IP degree of protection Busbar description Insulated bar

Set of 1

Complementary

Poles description	4P
Installation direction	Vertical, operating position: rear
Installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
T102	Pack enclosure
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[le] rated operational current	160 A
[lcw] rated short-time withstand current	10 kA (1 s)
[lpk] rated peak withstand current	30 kA
I²t on activation	100000 kA².s
Permissible current	160 A
Length	1000 mm
Height	85 mm
Depth	45 mm
Net weight	3.98 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm

Quantity per set

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA
Mechanical robustness	Seismic tests structure reinforcement - 2.5G conforming to IEC 60068-2-57

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.500 cm	
Package 1 Width	13.000 cm	
Package 1 Length	113.000 cm	

Package 1 Weight	4.221 kg
Unit Type of Package 2	P12
Number of Units in Package 2	48
Package 2 Height	50.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	204.000 kg

Offer Sustainability

Green Premium product
☑ REACh Declaration
Compliant with Exemptions
Yes
☑ China RoHS Declaration
€Yes
No need of specific recycling operations
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Yes