

AP DK4 BL**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Partition plates and end plates are essential accessories for terminal blocks. Partition plates provide optical and electrical separation of different potentials and functional groups, increasing safety and ensuring a clear structure inside the control cabinet. End plates close the terminal block row on the sides, protect against contact with live parts, and ensure a clean, stable finish. Both components are precisely matched to the respective Weidmüller terminal block series, contributing to safe, compliant, and professional wiring.

General ordering data

| | |
|---------------------|---|
| Version | End plate for terminals, blue, Height: 50 mm, Width: 1.5 mm, V-2, PA 66, Snap-on: Yes |
| Order No. | 0359280000 |
| Type | AP DK4 BL |
| GTIN (EAN) | 4008190031213 |
| Qty. | 20 items |
| Delivery status | This article will no longer be available in the future. |
| Available until | 2026-06-30T00:00:00+02:00 |
| Alternative product | AP DK4 |

AP DK4 BL

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

ROHS Conform

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 41.2 mm | Depth (inches) | 1.622 inch |
| Height | 50 mm | Height (inches) | 1.9685 inch |
| Width | 1.5 mm | Width (inches) | 0.0591 inch |
| Net weight | 2.25 g | | |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature | -25 °C...55 °C | Ambient temperature | -5 °C...40 °C |
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |

Environmental Product Compliance

| | | | |
|--------------------------|-----------------------------|-----------------|--|
| RoHS Compliance Status | Compliant without exemption | | |
| REACH SVHC | No SVHC above 0.1 wt% | | |
| Product Carbon Footprint | Cradle to gate | 0.021 kg CO2eq. | |

Material data

| | | | |
|---------------------------|-------|--------|------|
| Basic material | PA 66 | Colour | blue |
| UL 94 flammability rating | V-2 | | |

System specifications

Version End plate

Additional technical data

Snap-on Yes Installation advice Direct mounting

General

Installation advice Direct mounting

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000886 | ETIM 9.0 | EC000886 |
| ETIM 10.0 | EC000886 | ECLASS 14.0 | 27-25-03-01 |
| ECLASS 15.0 | 27-25-03-01 | | |