

Data sheet

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

Page 1/6

P/N


15090076-50

EAN 4251122189418


2026/08/24

Version: O

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- LC duplex plastic adapter, SC simplex design with metal clip
- slotted ceramic guide sleeves for single mode and multimode applications
- with transparent dust protection caps for a better visibility during red light test
- high material stability, surface quality and durability
- durability min. 1000 mating cycles with a ceramic guide sleeve
- screws and nuts included
- variants: blue (OS2), green (OS2 APC), lime green (OM5), violet (OM4), aqua (OM3), each variant available in packing units of 1 piece or 50 pieces



Data sheet

Page 2/6

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

P/N

15090076-50

EAN 4251122189418

2026/08/24

Version: O

Technical Data

General Data

Fields of application	structured building cabling fiber to the desk data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	coupler / adapter (FO)
Transmission technology	Fiber optic
Color	green
Dimensions	
Dimension (L x W x H)	29.2 mm x 12.8 mm x 9.4 mm
Dimension (L x W x H)	1.15 in. x 0.504 in. x 0.37 in.
Mode type of the fiber	Singlemode
Shape	APC (Angled Physical Contact)
Labeling option	on housing

Connections/interfaces

Connector interfaces	LC
----------------------	----

Mechanical data

Cut-out	SC, LC-D, E2000
Connector type	duplex
Mounting method	latchable and screwable
Life - Number of mating cycles	min. 1000
Position/mounting of latch standard installation position	top

Materials and material properties

Material - Housing	Plastics
Material - Sleeve	ceramic, slotted
Halogen free	yes
RoHS	compliant



Data sheet

Page 3/6

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

P/N

15090076-50

EAN 4251122189418

2026/08/24

Version: O

Technical Data

Standards/Regulations

Fibre optic connector interfaces LC - IEC 61754-20

Classifications

ETIM 7.0 EC000752

ETIM 8.0 EC000752

ETIM 9.0 EC000752

ETIM 10.0 EC000752

Packing details

Type of packaging 1 pc(s) / plastic bag

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.



Data sheet

Page 4/6

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

P/N

15090076-50

EAN 4251122189418

2026/08/24

Version: O

Accessories

P/N	Designation
1502007300-E	OpDAT PF patch panel for 24xLC-D/SC-S/E2000-S
1502200200-E	OpDAT PA patch panel unequipped for 24xLC-D/SC-S/E2000, gray
15024A0200-E	OpDAT REGpro front cover for 12xE2000/12xSC-S
1502507300-E	OpDAT fix patch panel for 24xLC-D/SC-S/E2000



Data sheet

Page 5/6

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

P/N

15090076-50

EAN 4251122189418

2026/08/24

Version: O

Accessories from

P/N	Designation
14040000-E	MCO IP69k protective housing for outdoor use, set for exposed installation
14040010-E	MCO IP69k Protective housing for outdoor use, set with mounting bracket
14040100-E	MCO IP69k Protective housing for outdoor use, set wall/ housing bushing



Data sheet

Page 6/6

OpDAT adapter LC-Duplex APC OS2 - 50 pieces

P/N

15090076-50

EAN 4251122189418

2026/08/24

Version: O

Illustrations

Dimensional drawing

