



## Main

Range	Acti9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	12

## Complementary

Number of ways	12 ways N + 1 L
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm between phase and neutral
Connector type	Tooth
Distance between way	18 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	End-pieces Tooth covers
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	400 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	4 kV
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Height	32 mm
Width	218 mm
Depth	27 mm
Net weight	93 g
Colour	White (RAL 9003)
Range compatibility	Acti 9 Acti9 C40 Acti 9 Acti9 C40 Vigi Acti 9 Acti9 iDPN Acti 9 Acti9 iDPN Vigi Acti 9 Acti9 IDC Multi9 Multi9 N40 Multi9 Multi9 N40 Vigi Acti9 Acti9 iC40 Acti9 Acti9 iCV40 Acti9 Vigi iCG40 Acti9 Acti9 iID40

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.






## Environment

Standards	EN/IEC 60439-1
Fire resistance	960 °C ( 30 s ) conforming to IEC 60695-2-1
Pollution degree	3 conforming to EN/IEC 60439-1
IP degree of protection	IP20 with end-pieces and tooth covers

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.200 cm
Package 1 Width	2.700 cm
Package 1 Length	27.200 cm
Package 1 Weight	90.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	5.200 cm
Package 2 Width	16.000 cm
Package 2 Length	30.500 cm
Package 2 Weight	1.146 kg
Unit Type of Package 3	S06
Number of Units in Package 3	720
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	82.180 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins