

# LUFS 10.00/02/180V 5.0SN BK BX

**Weidmüller Interface GmbH & Co. KG**


Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Product image



High-performance PCB terminal with a PUSH IN connection system for conductor cross-sections up to 16 mm<sup>2</sup>.

- Fast connection without tools thanks to pushers to open the contact point, or direct plug-in method
- Securely closed contact point, with the "Connection Safety Concept" the conductor is always clamped securely
- Integrated test point for PS 2.0 test plug
- Central tip test point for test probes on the upper side of the terminal
- Increased derating reserves because WEMID insulating material is used.
- Conductor outlet direction of 180°

## General ordering data

|              |                                                                                                                                                                                         |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version      | Printed circuit board terminals, 10.00 mm, Number of poles: 2, 180°, Solder pin length (l): 5 mm, tinned, black, PUSH IN with actuator, Clamping range, max. : 16 mm <sup>2</sup> , Box |
| Order No.    | <a href="#">2492110000</a>                                                                                                                                                              |
| Type         | LUFS 10.00/02/180V 5.0SN BK BX                                                                                                                                                          |
| GTIN (EAN)   | 4050118559842                                                                                                                                                                           |
| Qty.         | 40 pc(s).                                                                                                                                                                               |
| Product data | IEC: 1000 V / 101 A / 0.5 - 25 mm <sup>2</sup><br>UL: 600 V / 57 A / AWG 18 - AWG 4                                                                                                     |
| Packaging    | Box                                                                                                                                                                                     |

Creation date May 11, 2025 9:17:26 PM CEST

**LUFS 10.00/02/180V 5.0SN BK BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Technical data**
**Dimensions and weights**

|                          |           |                 |            |
|--------------------------|-----------|-----------------|------------|
| Depth                    | 24.7 mm   | Depth (inches)  | 0.972 inch |
| Height                   | 36.3 mm   | Height (inches) | 1.429 inch |
| Height of lowest version | 31.3 mm   | Width           | 21.58 mm   |
| Width (inches)           | 0.85 inch | Net weight      | 16.909 g   |

**System parameters**

|                                              |                            |                                            |                              |
|----------------------------------------------|----------------------------|--------------------------------------------|------------------------------|
| Product family                               | OMNIMATE Power - series LU | Wire connection method                     | PUSH IN with actuator        |
| Mounting onto the PCB                        | THT solder connection      | Conductor outlet direction                 | 180°                         |
| Pitch in mm (P)                              | 10 mm                      | Pitch in inches (P)                        | 0.394 "                      |
| Number of poles                              | 2                          | Pin series quantity                        | 1                            |
| Fitted by customer                           | No                         | Number of rows                             | 1                            |
| Solder pin length (l)                        | 5 mm                       | Solder pin dimensions                      | d = 1.2 mm, Octagonal        |
| Solder eyelet hole diameter (D)              | 1.6 mm                     | Solder eyelet hole diameter tolerance (D)+ | 0, 1 mm                      |
| Number of solder pins per pole               | 2                          | Screwdriver blade                          | 0.8 x 4.0                    |
| Stripping length                             | 18 mm                      | L1 in mm                                   | 10 mm                        |
| L1 in inches                                 | 0.394 "                    | Touch-safe protection acc. to DIN VDE 0470 | IP20 plugged/ IP10 unplugged |
| Touch-safe protection acc. to DIN VDE 57 106 | Safe from finger touch     | Protection degree                          | IP20                         |

**Material data**

|                                  |            |                                      |                   |
|----------------------------------|------------|--------------------------------------|-------------------|
| Insulating material              | Wemid (PA) | Colour                               | black             |
| Colour chart (similar)           | RAL 9011   | Insulating material group            | I                 |
| Comparative Tracking Index (CTI) | ≥ 600      | UL 94 flammability rating            | V-0               |
| Contact base material            | E-Cu       | Contact material                     | Cu-alloy          |
| Contact surface                  | tinned     | Layer structure of solder connection | 4...10 µm Sn matt |
| Storage temperature, min.        | -40 °C     | Storage temperature, max.            | 70 °C             |
| Operating temperature, min.      | -40 °C     | Operating temperature, max.          | 120 °C            |

**Conductors suitable for connection**

|                                                                     |                         |
|---------------------------------------------------------------------|-------------------------|
| Clamping range, min.                                                | 0.5 mm <sup>2</sup>     |
| Clamping range, max.                                                | 16 mm <sup>2</sup>      |
| Wire connection cross section AWG, min.                             | AWG 18                  |
| Wire connection cross section AWG, max.                             | AWG 4                   |
| Solid, min. H05(07) V-U                                             | 0.5 mm <sup>2</sup>     |
| Solid, max. H05(07) V-U                                             | 16 mm <sup>2</sup>      |
| Stranded, min. H07V-R                                               | 6 mm <sup>2</sup>       |
| Stranded, max. H07V-R                                               | 25 mm <sup>2</sup>      |
| Flexible, min. H05(07) V-K                                          | 0.5 mm <sup>2</sup>     |
| Flexible, max. H05(07) V-K                                          | 25 mm <sup>2</sup>      |
| w. plastic collar ferrule, DIN 46228 pt 4, 0.5 mm <sup>2</sup> min. |                         |
| w. plastic collar ferrule, DIN 46228 pt 4, 16 mm <sup>2</sup> max.  |                         |
| w. wire end ferrule, DIN 46228 pt 1, min.                           | 0.5 mm <sup>2</sup>     |
| w. wire end ferrule, DIN 46228 pt 1, max.                           | 16 mm <sup>2</sup>      |
| Plug gauge in accordance with EN 60999 a x b; ø                     | 5.4 mm x 5.1 mm; 5.3 mm |

Creation date May 11, 2025 9:17:26 PM CEST

**LUFS 10.00/02/180V 5.0SN BK BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Technical data**

|                     |                                                                                                                                                                        |                              |                             |       |  |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------|-------|--|
| Clampable conductor | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 2.5 mm²                     |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 20 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H2.5/25D BL</a> |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H2.5/18</a>     |       |  |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 4 mm²                       |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 20 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H4.0/26D GR</a> |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H4.0/18</a>     |       |  |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 6 mm²                       |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 20 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H6.0/26 SW</a>  |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H6.0/18</a>     |       |  |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 10 mm²                      |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 21 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H10.0/28 EB</a> |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H10.0/18</a>    |       |  |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 16 mm²                      |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 21 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H16.0/28 GN</a> |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H16.0/18</a>    |       |  |
|                     | Cross-section for conductor connection                                                                                                                                 | Type                         | fine-wired                  |       |  |
|                     |                                                                                                                                                                        | nominal                      | 1.5 mm²                     |       |  |
|                     | wire end ferrule                                                                                                                                                       | Stripping length             | nominal                     | 20 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H1.5/24 R</a>   |       |  |
|                     |                                                                                                                                                                        | Stripping length             | nominal                     | 18 mm |  |
|                     |                                                                                                                                                                        | Recommended wire-end ferrule | <a href="#">H1.5/18</a>     |       |  |
| Reference text      | Length of ferrules is to be chosen depending on the product and the rated voltage., The outside diameter of the plastic collar should not be larger than the pitch (P) |                              |                             |       |  |

**LUFS 10.00/02/180V 5.0SN BK BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Technical data**
**Rated data acc. to IEC**

|                                                                           |               |                                                                       |         |
|---------------------------------------------------------------------------|---------------|-----------------------------------------------------------------------|---------|
| tested acc. to standard                                                   | IEC 60947-7-4 | Rated current, min. number of poles (Tu=20°C)                         | 101 A   |
| Rated current, max. number of poles (Tu=20°C)                             | 85.8 A        | Rated current, min. number of poles (Tu=40°C)                         | 101 A   |
| Rated current, max. number of poles (Tu=40°C)                             | 76 A          | Rated voltage for surge voltage class / pollution degree II/2         | 1,000 V |
| Rated voltage for surge voltage class / pollution degree III/2            | 1,000 V       | Rated voltage for surge voltage class / pollution degree III/3        | 1,000 V |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 6 kV          | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 8 kV    |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 8 kV          |                                                                       |         |

**Rated data acc. to CSA**

|                                   |        |                                   |       |
|-----------------------------------|--------|-----------------------------------|-------|
| Rated voltage (Use group B / CSA) | 600 V  | Rated voltage (Use group C / CSA) | 600 V |
| Rated voltage (Use group D / CSA) | 600 V  | Rated current (Use group B / CSA) | 57 A  |
| Rated current (Use group C / CSA) | 57 A   | Rated current (Use group D / CSA) | 5 A   |
| Wire cross-section, AWG, min.     | AWG 18 | Wire cross-section, AWG, max.     | AWG 4 |

**Rated data acc. to UL 1059**

|                                       |                                                                                     |                                       |         |
|---------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------|---------|
| Institute (cURus)                     |  | Certificate No. (cURus)               | E60693  |
| Rated voltage (Use group B / UL 1059) | 600 V                                                                               | Rated voltage (Use group C / UL 1059) | 600 V   |
| Rated voltage (Use group D / UL 1059) | 600 V                                                                               | Rated voltage (Use group F / UL 1059) | 1,000 V |
| Rated current (Use group B / UL 1059) | 57 A                                                                                | Rated current (Use group C / UL 1059) | 57 A    |
| Rated current (Use group D / UL 1059) | 5 A                                                                                 | Rated current (Use group F / UL 1059) | 57 A    |
| Wire cross-section, AWG, min.         | AWG 18                                                                              | Wire cross-section, AWG, max.         | AWG 4   |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate.              |                                       |         |

**Packing**

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 233 mm |
| VPE width | 132 mm | VPE height | 47 mm  |

**Type tests**

|                              |            |                                                                          |
|------------------------------|------------|--------------------------------------------------------------------------|
| Test: Durability of markings | Standard   | IEC 60947-1 section 8.2.4.5.1 / 06.07, IEC 60512-1-1:2002-02             |
|                              | Test       | mark of origin, type identification, pitch, durability, stripping length |
|                              | Evaluation | available                                                                |

**LUFS 10.00/02/180V 5.0SN BK BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Technical data**

|                                                           |                |                                                                              |
|-----------------------------------------------------------|----------------|------------------------------------------------------------------------------|
| Test: Clampable cross section                             | Standard       | IEC 60999-1 section 7 and 9.1 / 11.99, IEC 60947-1 section 8.2.4.5.1 / 03.11 |
|                                                           | Conductor type | Type of conductor and solid 0.5 mm <sup>2</sup> conductor cross-section      |
|                                                           |                | Type of conductor and stranded 0.5 mm <sup>2</sup> conductor cross-section   |
|                                                           |                | Type of conductor and solid 16 mm <sup>2</sup> conductor cross-section       |
|                                                           |                | Type of conductor and stranded 16 mm <sup>2</sup> conductor cross-section    |
|                                                           |                | Type of conductor and H07V-U16 conductor cross-section                       |
|                                                           |                | Type of conductor and H07V-U6 conductor cross-section                        |
|                                                           |                | Type of conductor and H07V-K16 conductor cross-section                       |
|                                                           |                | Type of conductor and AWG 4 conductor cross-section                          |
|                                                           | Evaluation     | passed                                                                       |
| Test for damage to and accidental loosening of conductors | Standard       | IEC 60999-1 section 9.4 / 11.99                                              |
|                                                           | Requirement    | 0.3 kg                                                                       |
|                                                           | Conductor type | Type of conductor and AWG 20/1 conductor cross-section                       |
|                                                           |                | Type of conductor and AWG 20/19 conductor cross-section                      |
|                                                           |                | Type of conductor and H05V-U0.5 conductor cross-section                      |
|                                                           |                | Type of conductor and H05V-K0.5 conductor cross-section                      |
|                                                           | Evaluation     | passed                                                                       |
|                                                           | Requirement    | 2.9 kg                                                                       |
|                                                           | Conductor type | Type of conductor and H07V-U16 conductor cross-section                       |
|                                                           |                | Type of conductor and H07V-K16 conductor cross-section                       |
|                                                           | Evaluation     | passed                                                                       |
|                                                           | Requirement    | 4,5 kg                                                                       |
|                                                           | Conductor type | Type of conductor and AWG 4/7 conductor cross-section                        |
|                                                           |                | Type of conductor and AWG 4/19 conductor cross-section                       |
|                                                           | Evaluation     | passed                                                                       |

**LUFS 10.00/02/180V 5.0SN BK BX**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)
**Technical data**

|               |                |                                                         |
|---------------|----------------|---------------------------------------------------------|
| Pull-out test | Standard       | IEC 60999-1 section 9.5 / 11.99                         |
|               | Requirement    | ≥20 N                                                   |
|               | Conductor type | Type of conductor and AWG 20/1 conductor cross-section  |
|               |                | Type of conductor and AWG 20/19 conductor cross-section |
|               |                | Type of conductor and H05V-U0.5 conductor cross-section |
|               |                | Type of conductor and H05V-K0.5 conductor cross-section |
|               | Evaluation     | passed                                                  |
|               | Requirement    | ≥100 N                                                  |
|               | Conductor type | Type of conductor and H07V-U16 conductor cross-section  |
|               |                | Type of conductor and H07V-K16 conductor cross-section  |
|               | Evaluation     | passed                                                  |
|               | Requirement    | ≥ 135 N                                                 |
|               | Conductor type | Type of conductor and AWG 4/7 conductor cross-section   |
|               |                | Type of conductor and AWG 4/19 conductor cross-section  |
|               | Evaluation     | passed                                                  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002643    | ETIM 7.0    | EC002643    |
| ETIM 8.0    | EC002643    | ETIM 9.0    | EC002643    |
| ETIM 10.0   | EC002643    | ECLASS 9.0  | 27-44-04-01 |
| ECLASS 9.1  | 27-44-04-01 | ECLASS 10.0 | 27-44-04-01 |
| ECLASS 11.0 | 27-46-01-01 | ECLASS 12.0 | 27-46-01-01 |
| ECLASS 13.0 | 27-46-01-01 | ECLASS 14.0 | 27-46-01-01 |
| ECLASS 15.0 | 27-46-01-01 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

# LUFS 10.00/02/180V 5.0SN BK BX

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Important note

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Notes          | <ul style="list-style-type: none"> <li>• Additional variants on request</li> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <li>• P on drawing = pitch</li> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> <li>• The test point can only be used as potential-pickup point.</li> <li>• The single-position PCB terminal block can be used for voltages up to 1500 V (DC) and 1000 V (AC). The relevant device standard and the appropriate required clearances and creepage distances should be observed in the application</li> <li>• Long term storage of the product with average temperature of 50 °C and maximum humidity 70%, 36 months</li> </ul> |

### Approvals

Approvals



|                         |                                                                                                                                                                             |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID         | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/</a> |
| ROHS                    | Conform                                                                                                                                                                     |
| UL File Number Search   | UL Website                                                                                                                                                                  |
| Certificate No. (cURus) | E60693                                                                                                                                                                      |

### Downloads

|                                             |                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a>                                                                                                                                                                                                                                                                                                                     |
| Engineering Data                            | <a href="#">CAD data – STEP</a>                                                                                                                                                                                                                                                                                                                                     |
| Product Change Notification                 | <a href="#">20210909 Color Change of Actuator to LLF(S) and LUF(S) Family</a><br><a href="#">20210909 LLF(S) und LUF(S) Familie - Farbänderung des Betätigungselementes</a><br><a href="#">Optimierung des QR-Codes auf den Produkten der OMNIMATE Power Leiterplattenanschlussklemmen</a><br><a href="#">Optimization QR- Code on OMNIMATE POWER PCB Terminals</a> |
| User Documentation                          | <a href="#">QR-Code product handling video</a><br><a href="#">Assembly instruction_Montageanleitung_LLFS_LUFS_EN_DE</a>                                                                                                                                                                                                                                             |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>                                                                                                                                                                                                                                                                                                                            |


## LUFS 10.00/02/180V 5.0SN BK BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany


[www.weidmueller.com](http://www.weidmueller.com)

## Drawings


### Product image




### Dimensional drawing




### Derating curve



### Derating curve



### Derating curve



### Product benefits




Power up to UL 600 V  
Offset solder pins

**LUFS 10.00/02/180V 5.0SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold


Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Slotted screwdriver**

VDE insulated slot-head screwdriver, SDI DIN 7437, ISO 2380/2, drive output acc. to DIN 5264, ISO 2380/1. SoftFinish grip

**General ordering data**

|            |                            |                          |
|------------|----------------------------|--------------------------|
| Type       | SDIS 0.8X4.0X100           | Version                  |
| Order No.  | <a href="#">9008400000</a> | Screwdriver, Screwdriver |
| GTIN (EAN) | 4032248056361              |                          |
| Qty.       | 1 pc(s).                   |                          |

**Slotted screwdriver**

Slotted screwdriver with rounded blade SD DIN 5265, ISO 2380/2, output to DIN 5264, ISO 2380/1. ChromTop tip, SoftFinish grip

**General ordering data**

|            |                            |                          |
|------------|----------------------------|--------------------------|
| Type       | SDS 0.8X4.0X100            | Version                  |
| Order No.  | <a href="#">9008340000</a> | Screwdriver, Screwdriver |
| GTIN (EAN) | 4032248056293              |                          |
| Qty.       | 1 pc(s).                   |                          |

**LUFS 10.00/02/180V 5.0SN BK BX****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Accessories****Additional accessories****No task is too small when creating the perfect solution.**

Connections form just one part of the overall process. Small details are often the key to the perfect solution in applications where potentials are tested, grouped or even isolated.

A system is not a system without small but essential details:

- Test plugs ensure reliable pick-up from diagnostic sockets

In tandem with the manufacturing process and application.

**General ordering data**

| Type       | PS 2.0 MC                  | Version                                                                | Product data | Packaging |
|------------|----------------------------|------------------------------------------------------------------------|--------------|-----------|
| Order No.  | <a href="#">0310000000</a> | PCB plug-in connector, Accessories, Test plug, red, Number of poles: 1 |              | Box       |
| GTIN (EAN) | 4008190000059              |                                                                        |              |           |
| Qty.       | 20 pc(s).                  |                                                                        |              |           |


### LUFS 10.00/02/180V 5.0SN BK BX

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Product benefits




Simple actuation of the contact point


## Recommended wave soldering profiles

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

### Single Wave:



### Double Wave:



### Wave soldering profiles

Wired connection elements should be processed in accordance with the DIN EN 61760-1 standard. We have included two recommendations for practical wave soldering profiles, with which Weidmüller PCB terminals and connectors are qualified.

When choosing a suitable profile for your application, the following factors also need to be considered:

- PCB thickness
- Proportion of Cu in the layers
- Single/double-sided assembly
- Product range
- Heating and cooling rates

The single and double wave profiles each indicate the recommended operating range, including the maximum soldering temperature of 260°C. In practice, the maximum soldering temperature is quite often well below the above maximum profile.

We reserve the right to make technical changes.