
Main cable junction terminal

HA 25-43



HA 25-43

Main cable junction terminal

Productnumber: 69143301
Dimensions: 50 x 50 x 100 mm

Main line T-piece terminal with 4 clamping points
1.5-25 mm² per pole

4-pole - finger proof

Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

Technical Data

electrical characteristics

Rated operating voltage AC:	400 V
Number of poles:	4
Connection 1: Connection type:	Screws
Connection 1: Clamping points per pole:	4
Connection 1: Suitable for Cu conductors:	1
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (min):	2.5 mm²
Connection 1: Connectable conductor cross-section, fine-wire with ferrule (max):	16 mm²
Connection 1: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 1: Connectable conductor cross-section, single-wire (max):	25 mm²
Connection 1: Connectable conductor cross-section, stranded (min):	1.5 mm²
Connection 1:Connectable conductor cross-section, stranded (max):	25 mm²
Connection 2: Connection type:	Screws
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (min):	1.5 mm²
Connection 2: Connectable conductor cross-section, fine-wire with ferrule (max):	10 mm²
Connection 2: Connectable conductor cross-section, single-wire (min):	1.5 mm²
Connection 2: Connectable conductor cross-section, single-wire (max):	16 mm²
Connection 2: Connectable conductor cross-section, stranded (min):	1.5 mm²
Connection 2: Connectable conductor cross-section, stranded (max):	16 mm²

Dimensions

Width:	50 mm
Length:	50 mm
Height:	100 mm
Weight:	0.243 kg

Material characteristics

Flammability class according with UL94:	V0
Glow-wire flammability:	960 °C (EN 60695-2-11)

mechanical properties

Connection 1: Tightening moment:	2.5 Nm
Connection 2: Tightening torque:	2.5 Nm

Sales Information

EAN:	4013902014224
ETIM Class:	EC000275
Custom tariff number:	85369010
Minimum order quantity:	2