

GWDR M50-W



In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	in closed state, M 50, Nylon 6
Order No.	1185650000
Type	GWDR M50-W
GTIN (EAN)	4050118078312
Qty.	25 items

GWDR M50-W

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

ROHS Conform

Dimensions and weights

Diameter 50 mm Net weight 70 g

Temperatures

Operating temperature -50 °C...120 °C

Environmental Product Compliance

RoHS Compliance Status Compliant without exemption
 REACH SVHC No SVHC above 0.1 wt%

General information

O.D.	65 mm	UL 94 flammability rating	V-0
Operating temperature range, max.	120 °C	Operating temperature range, min.	-50 °C
Halogen	halogen-free	Thickness	2.00 mm
Cable gland	M 50	Basic material	Nylon 6
Diameter of sealing ring	50.00 mm	External thread	M 50
Inside diameter D2	50.30 mm		

Classifications

ETIM 8.0	EC001181	ETIM 9.0	EC001181
ETIM 10.0	EC001181	ECLASS 14.0	27-43-03-19
ECLASS 15.0	27-43-03-19		