
Empty enclosure

AL 1506-3



AL 1506-3

Empty enclosure

CUSTOMIZABLE

Productnumber: 15000401
Dimensions: 150 x 64 x 34 mm

Empty enclosure, protection class IP66, Aluminium, powder-coated painting, internal fixing points, for installations in industrial environments and protected outdoor areas

Box: Aluminium, powder-coated painting, Lid: Aluminium, powder-coated painting, silver-grey, smooth sidewalls

IP66 IK09

Technical Data

electrical characteristics

Protection class:	I
Type of protection:	IP66
UL Type Rating:	not specified

Colours

Cover colour:	silver-grey

Dimensions

Width:	150 mm
Length:	64 mm
Height:	34 mm
Weight:	0.2874 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK09
Cover screw torque:	2.5 Nm
Stackable:	no
Type of top part:	Cover
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	75 °C

Ambient conditions

24h ambient temperature:	60 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902678655
ETIM Class:	EC000261
Custom tariff number:	85369095
Minimum order quantity:	1

Material

Base unit material:	Aluminium, powder-coated painting
Cover material:	Aluminium, powder-coated painting
Sealing material:	Polyurethane

Accessories

15400401 - AL ALS-kl - External attachment set