

PV XSTU06 STOEVO2-C250

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com



The extension cable is used to connect several elements of a PV system, e.g. for the connection between PV panels, inverters and surge protection boxes. The cables are available in different connection variants.

General ordering data

Version	Photovoltaics, Y connector, Cable end open
Order No.	3018470250
Type	PV XSTU06 STOEVO2-C250
GTIN (EAN)	4099986930377
Qty.	1 items

PV XSTU06 STOEVO2-C250

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 1 g

Environmental Product Compliance

RoHS Compliance Status Compliant with exemption

RoHS Exemption (if applicable/known) 6c

REACH SVHC Lead 7439-92-1

PV cable harnessing

PV cable version	Cable side	left
	Number	1
	Cable length	2500 mm
	Cable colour	black
	Cable cross section	6 mm ²
	Inline fuse integrated	No
	Connector version	MC4-Evo 2
	Type of plug-in contact	male
	Cable side	right
	Version of cable end [In-Block)	free conductor end
Rated DC voltage	1500 V	
Wire cross-section	6.00 mm ²	

Electrical characteristics

Rated DC voltage 1500 V

Classifications

ETIM 8.0	EC001576	ETIM 9.0	EC001576
ETIM 10.0	EC001576	ECLASS 14.0	27-06-04-02
ECLASS 15.0	27-06-04-02		