
Junction box

Q-Mini-L



Q-Mini-L

Junction box

Productnumber: 33490801
Dimensions: 89 x 43 x 34 mm

Junction box, protection class IP20, nominal cross-section 2.5 mm², Ui=400 V AC, certified by VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), inserts with cable retention capacity, (2 rear, 8 side), external fixing lugs, for standard indoor installations, with cable retention, cable entry from above possible

grey, without terminals

IP20 | 2,5² | IK07 | 400V AC

Technical Data

electrical characteristics

Rated insulation voltage AC:	400 V
Max. conductor cross section:	2,5 mm²
Protection class:	II
Type of protection:	IP20
Terminal type:	none
UL Type Rating:	not specified

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	89 mm
Length:	43 mm
Height:	34 mm
Inner length:	33 mm
Inner width:	79 mm
Inner height:	29 mm
Weight:	0.0274 kg

Material characteristics

UV-resistant:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability:	650 °C (EN 60695-2-11)

Max. number of terminals per cross section acc. to DIN VDE 0606-1

max. amount of terminals at 1,5²:	5
max. amount of terminals at 2,5²:	3

Max. number of wires per cross section acc. to DIN VDE 0606-1

max. amount of wires at 1,5²:	15
max. amount of wires at 2,5²:	9

mechanical properties

Impact strength:	IK07
Sealable:	no
Type of fastening:	Wall/ceiling mounting
Fastening:	external fixing lugs

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	Indoors

Sales Information

EAN:	4013902642311
ETIM Class:	EC002600
Custom tariff number:	85389099
Minimum order quantity:	10

Material

Base unit material:	Polypropylene
Cover material:	Polypropylene

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))

Accessories

89601901 - KTB 2 - Cable tray fastening

89602901 - KTB 1-100 - Cable tray fastening

Cable gland

