

A9F06606

Miniature circuit breaker (MCB), Acti9 iC60H, 1P+N, 6A, B curve, 10000A (60898-1), 15kA (60947-2), double term.



Hoofd

Device application	Distributie
Range	Acti 9
Product name	Acti 9 iC60
Product or component type	Miniatuur vermogensschakelaar
Device short name	iC60H
Poles description	1P + N
Number of protected poles	1
Neutral position	Links
[In] rated current	6 A
Network type	DC AC
Trip unit technology	Thermisch-magnetisch
Curve code	B
Breaking capacity	10000 A Icn bij 230 V AC 50/60 Hz conform aan EN/IEC 60898-1 15 KA Icu bij 220...240 V AC 50/60 Hz conform aan EN/IEC 60947-2 42 KA Icu bij 12...60 V AC 50/60 Hz conform aan EN/IEC 60947-2 30 kA Icu bij 100...133 V AC 50/60 Hz conform aan EN/IEC 60947-2
Utilisation category	A conform aan EN 60898-1 A conform aan IEC 60898-1
Suitability for isolation	Ja conform aan EN 60898-1 Ja conform aan EN 60947-2 Ja conform aan IEC 60898-1 Ja conform aan IEC 60947-2
Standards	EN 60947-2 IEC 60947-2 EN 60898-1 IEC 60898-1

Complementair

Network frequency	50/60 Hz
Magnetic tripping limit	4 x In +/- 20 %
Ics dienst onderbrekingsvermogen	21 KA 50 % conform aan EN 60947-2 - 12...60 V AC 50/60 Hz 7,5 KA 50 % conform aan EN 60947-2 - 220...240 V AC 50/60 Hz 21 KA 50 % conform aan IEC 60947-2 - 12...60 V AC 50/60 Hz 7,5 KA 50 % conform aan IEC 60947-2 - 220...240 V AC 50/60 Hz 7500 A 75 % conform aan EN 60898-1 - 230 V AC 50/60 Hz 7500 A 75 % conform aan IEC 60898-1 - 230 V AC 50/60 Hz 15 KA 50 % conform aan IEC 60947-2 - 100...133 V AC 50/60 Hz 15 KA 50 % conform aan EN 60947-2 - 100...133 V AC 50/60 Hz
Limitation class	3 conform aan EN 60898-1 3 conform aan IEC 60898-1
[Ui] rated insulation voltage	500 V AC 50/60 Hz conform aan EN 60947-2 500 V AC 50/60 Hz conform aan IEC 60947-2
[Uimp] rated impulse withstand voltage	6 KV conform aan EN 60947-2 6 kV conform aan IEC 60947-2
Contact position indicator	Ja
Control type	Omschakelen

Local signalling	Uitschakelindicator
Mounting support	DIN-rail
Aantal modules van 9 mm	4
Height	91 mm
Width	36 mm
Depth	78,5 mm
Net weight	0,25 kg
Colour	Wit
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Aansluitingen - aansluitklemmen	Dubbele klem (boven- of onderkant) 1...25 mm ² stijf Dubbele klem (boven- of onderkant) 1...16 mm ² flexibel
Wire stripping length	14 mm for boven- of onderkant connection
Tightening torque	2 N.m boven- of onderkant
Earth-leakage protection	Apart blok

Omgeving

IP beschermingsgraad	IP20 conforming to IEC 60529 IP20 conforming to EN 60529
Pollution degree	3
Overvoltage category	IV
Tropicalisation	2
Relative humidity	95 % bij 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,500 cm
Package 1 Width	7,500 cm
Package 1 Length	9,000 cm
Package 1 Weight	224,000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	8,500 cm
Package 2 Width	10,000 cm
Package 2 Length	22,000 cm
Package 2 Weight	1,407 kg
Unit Type of Package 3	S03
Number of Units in Package 3	66
Package 3 Height	30,000 cm
Package 3 Width	30,000 cm
Package 3 Length	40,000 cm
Package 3 Weight	15,878 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	 REACH-verklaring
EU-richtlijn RoHS	Voldoet aan vrijstellingen
Kwikvrij	Ja
RoHS-regulering China	 RoHS-verklaring China
Informatie over RoHS-vrijstelling	 Ja
Milieu Profiel	 Milieuprofiel Van Het Product

Circulair Profiel	Geen specifieke recycling vereist
WEEE	Het product moet op markten van de Europese Unie worden afgevoerd volgens specifieke afvalinzamelingsregels en mag nooit in een gewone vuilnisbak terechtkomen.