

SL764+ SM OP

Part number 3117922





IP 40 | CLASS I

Description

LED surface-mount luminaire for indoor, comprising:
- Extruded aluminium profile housing, anodised (EV1) or polyester powder coat, die-cast aluminium end caps, polyester powder coat
- Opal PMMA diffuser for optimal light distribution and uniformity
- Direct light distribution
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Continuous mounted options and many other configurations are available at www.light-performer.com

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC002892

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	4790	**Luminaire lumen output [lm]:**	4160
Luminaire wattage [W]:	29 W	**Luminous efficacy [lm/W]:**	143
CRI:	80	**Colour temperature [K]:**	3000
Colour / Finishing:	GR-EV1 / Anodised grey / Matt	**IP degree of protection:**	IP40
Impact resistance / impact energy:	IK05 0.7J xx3	**Protection class:**	I
Optic:	S/A - Symmetric direct	**Beam angle:**	2 x 48°/51°
Net weight [kg]:	3.563	**Overall length [mm]:**	1692
Overall width [mm]:	44	**Overall height [mm]:**	66

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Opal plastic	**Glow wire test [°C]:**	650 °C

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	220-240V 50/60Hz	**Power factor / COS Φ:**	0.9
Inrush current [A/µs]:	31 / 175	**C10 1.5 mm²:**	23
C16 2.5 mm²:	38	**B10 1.5 mm²:**	14
B16 2.5 mm²:	23		

Installation

Application area:	Indoor lighting	**Mounting type:**	Linear systems
Min. ambient temperature [°C]:	10	**Max. ambient temperature [°C]:**	40

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@50000h
Distribution of light emission:	Direct	**DFF - Downward Flux Fraction [%]:**	100
UFF - Upward Flux Fraction [%]:	0		

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com