

Data sheet

Page 1/7


**M12 Industrial Ethernet cable, D-coded, 1.0 m,
M12 plug straight - M12 jack straight, drag chain, PUR**

P/N
142M1D12010
EAN 4251394600161
2026/09/29
Version: T


Illustrations



Dimensional drawing



Cut-out



See enlarged drawings at the end of document

Product specification

Shielded PUR cable for safe and industrial data transmission in automation and fieldbus technology. The cable is CMX-verified and complies with Cat5e (electrical properties based on EN50288-2-1). Materials and constructional design allow increased mechanical stress (abrasion, bending, vibrations etc.) of the cable. Use in drag chains with up to 3 million bending cycles is possible without risk. Special properties: flame retardant, seawater resistant, recyclable, LABS-free, RoHS compliant, acid and alkali resistant, ozone resistant, UV resistant, hydrolysis resistant, drag chain compatible, halogen free, oil resistant, high flexibility, microbe resistant, UN ECER118, PROFINET Type C.

- Standard variants: 1.0 m, 2.0 m, 5.0 m, 10.0 m.
- Other cable lengths on request.



Data sheet

Page 2/7

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 plug straight - M12 jack straight, drag chain, PUR

P/N

142M1D12010

EAN 4251394600161

2026/09/29

Version: T

Technical Data

General Data	
Fields of application	Industrial Ethernet
Design	Ethernet-Connection line
Cable length (m)	1 m
Cable length (ft)	3.28 ft
Cable	
Cable Type	SF/FTP
Wiring	Profinet
Wire color	yellow, white, orange, blue
Color - cable jacket	green
Transmission properties	5e
Connection 1	
Shielding	shielded
Dimension (L x W x H)	50.5 mm x 15 mm x 15 mm
Dimension (L x W x H)	1.988 in. x 0.591 in. x 0.591 in.
Connection 2	
Shielding	shielded
Dimension (L x W x H)	52 mm x 21.5 mm x 21.5 mm
Dimension (L x W x H)	2.047 in. x 0.846 in. x 0.846 in.

Connections/interfaces

Cable	
Conductor cross section AWG	AWG 22/7
Conductor diameter (mm)	0.75 mm
Conductor diameter (inch)	0.03 in.
Outer diameter cable jacket (mm)	6.5 mm
Outer diameter cable jacket (inch)	0.256 in.
Connection 1	
Connector type	M12-plug
Coding	D-coded
Type of plug contact, field side	Male (plug)
Cable feed arrangement, field side	straight
Number of poles	4
Pin Assignment	1 YE, 2 WH, 3 OG, 4 BU



Data sheet

Page 3/7

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 plug straight - M12 jack straight, drag chain, PUR

P/N

142M1D12010

EAN 4251394600161

2026/09/29

Version: T

Technical Data

Connections/interfaces

Connection 1

Latching lever protection	no
Color of the cable boot	black

Connection 2

Connector type	M12-jack
Coding	D-coded
Type of plug contact, field side	Female (bus)
Cable feed arrangement, field side	straight
Number of poles	4
Pin Assignment	1 YE, 2 OG, 3 WH, 4 BU
Color of the cable boot	black

Electrical characteristics

Connection 1

Current carrying capacity per pin (at 40 °C)	4 A
--	-----

Connection 2

Current carrying capacity per pin (at 40 °C)	4 A
--	-----

Mechanical data

Cable

drag chain suitable	yes
Bending radius (fixed)	26 mm
Bending radius (moved)	52 mm
Number of alternating bending cycles (mechanical resistance) at:	3 million bending cycles
Alternating bending radius	100 mm
velocity	4 m/s
acceleration	4 m/s ²

Connection 1

Mechanical life	min. 100 mating cycles
-----------------	------------------------

Connection 2

Mechanical life	min. 100 mating cycles
-----------------	------------------------



Data sheet

Page 4/7

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 plug straight - M12 jack straight, drag chain, PUR

P/N

142M1D12010

EAN 4251394600161

2026/09/29

Version: T

Technical Data

Materials and material properties

Cable

Material - Cable jacket	PUR
Material - Wire insulation	FRNC
Flame retardancy	yes, according to IEC 60332-1-2

Connection 1

Material - Contact	CuZnPb (brass)
Material - Contact surface	Au (gold)
Material - Contact carrier	Plastics, PA, BK
Material - Body	Plastics, TPU, BK
Material - Cap nut	Metal, CuZn, nickel-plated

Connection 2

Material - Contact	CuZnPb (brass)
Material - Contact surface	Au (gold)
Material - Contact carrier	Plastics, PA, BK
Material - Body	Plastics, TPU, BK
Material - Flange housings	Metal, CuZn, nickel-plated
Material - Sealing (jack)	FPM/FKM
Material - Outer sealing	NBR

Environmental conditions

Cable

Temperature range (fixed)	-30 °C - max. 70 °C
Temperature range (fixed)	-22 °F - 158 °F

Connection 1

	-40 °C
	-40 °F
Protection category (mounted)	IP67 (-30 °C...+90 °C), IP65 (-40 °C...+90 °C)

Connection 2

Protection category (mounted)	IP67 (-30 °C...+90 °C), IP65 (-40 °C...+90 °C)
-------------------------------	--



Data sheet

Page 5/7

M12 Industrial Ethernet cable, D-coded, 1.0 m, M12 plug straight - M12 jack straight, drag chain, PUR

P/N

142M1D12010

EAN 4251394600161

2026/09/29

Version: T

Technical Data

Standards/Regulations	
Profinet	Type C
Classifications	
ETIM 9.0	EC002599
ETIM 10.0	EC002599
Packing details	
Type of packaging	1 pc(s) / plastic bag

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!



Data sheet

Page 6/7

**M12 Industrial Ethernet cable, D-coded, 1.0 m,
M12 plug straight - M12 jack straight, drag chain, PUR**

P/N

142M1D12010


EAN 4251394600161

2026/09/29


Version: T

Illustrations

Dimensional drawing



Cut-out



Data sheet

Page 7/7

**M12 Industrial Ethernet cable, D-coded, 1.0 m,
M12 plug straight - M12 jack straight, drag chain, PUR**

P/N

142M1D12010


EAN 4251394600161

2026/09/29

Version: T

Illustrations

Wiring diagram



Principle diagram

