



Description MINIATURE CIRCUIT BREAKER

Code MT 250

No. of poles 3P

No. modules 3

Rated current 10 A

Curve C

Rated voltage 230-400 V

|                                             |                                               |                                             |                   |
|---------------------------------------------|-----------------------------------------------|---------------------------------------------|-------------------|
| Standard                                    | EN 60898, EN 60947-2                          | Rated frequency (Hz)                        | 50/60 Hz          |
| Breaking capacity EN 60898 230V (Icn)       | 25000 A                                       | Breaking capacity EN 60898 400V (Icn)       | 25000 A           |
| Breaking capacity EN 60898 (Ics)            | 0.5 x Icn                                     | Breaking capacity IEC/EN 60947-2 230V (Icu) | 40 kA             |
| Breaking capacity IEC/EN 60947-2 400V (Icu) | 25 kA                                         | Breaking capacity IEC/EN 60947-2 (Ics)      | 50% Icu           |
| Insulation voltage (Ui)                     | 500 V                                         | Rated impulse withstand voltage (Uimp)      | 4 kV              |
| Minimum operating voltage                   | 12V ac/dc                                     | Maximum operating voltage                   | 440V AC / 220V DC |
| Electrical endurance                        | 10.000                                        | Mechanical endurance                        | 20.000            |
| Section rigid cable                         | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> |                                             |                   |
| Section flexible cable                      | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> |                                             |                   |
| Rated tightening torque                     | 2 Nm                                          | Operating temperature                       | -25 +60 °C        |
| Stocking temperature                        | -40°C + +70°C                                 | Electrocod                                  | 1411              |

## DIMENSIONAL

## STANDARDS/APPROVALS

