

Description Automatic reclosing device
 Code Autotest 4P
 Rated voltage AC 400 V
 Rated frequency (Hz) 50Hz
 Rated current 63 A
 Rated residual operating current 300 mA
 Type of residual current protection A [S]
 Number of poles 4P

ELECTRICAL CHARACTERISTICS		- MECHANICAL CHARACTERISTICS		-
Standard	IEC/EN 61008-1, IEC/EN 61008-2-1	Maximum operating frequency		30 oper./h
Distribution system	TT - TN-S	Mechanical endurance		4000
Insulation voltage (Ui)	500 V	Operating temperature		-25°C ÷ +60°C
Dielectric strength test voltage between pole and earth	2500 a.c. for 1 minute	Stocking temperature		-40°C ÷ +70°C
Rated impulse withstand voltage (Uimp)	4 kV	No. modules		7
Overvoltage category	III	Completeable with	RS485 BUS module GW90992	
Rated non-operating resistance between live parts and earth (Rdo)		- FEATURE AUXILIARY CONTACT		-
Rated operating resistance between live parts and earth (Rd)		Type of contacts	Photomos (potential free)	
AUTOTEST FUNCIONT		Operating modes	NO/NC/NC + pulse	
Autotest (automatic RCCB protection test)	Yes	Voltage operating	5-230 V ac/dc	
RESTART FUNCTIONFUN		Operating frequency	50 Hz	
Automatic reclosure for untimely tripping	No	Current operating	0.6mA (min)-100mA cosφ= 1 (max)	
Earth failure test	No	Use category	AC12	
Continuous system monitoring	No	Terminal section	≤ 2,5 mm²	

DIMENSIONAL

STANDARDS/APPROVALS

