# A9A26959

undervoltage release, Acti9, iMN, voltage release, 115 V AC





#### Main

Widin	
Range of product	Acti9
Product or component type	Undervoltage release
Device short name	iMN
[Uc] control circuit voltage	115 V AC 400 Hz
Control type	Standard
9 mm pitches	2

### Complementary

Range compatibility	Acti 9 Acti9 iC65
	Acti 9 Acti9 ARA
	Acti 9 Acti9 iDPN Vigi
	Acti 9 Acti9 iID
	Acti 9 Acti9 iSW-NA
	Acti 9 Acti9 RCA
	Acti 9 Acti9 iDPN (China version)
	Acti 9 Acti9 iC60 double terminals miniature circuit breaker
	Acti 9 Acti9 iC40
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top and bottom: YES
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal - 1 cable(s) 7 mm² - rigid
	Clamp terminal - 2 cable(s) 2.6 mm <sup>2</sup> - rigid
	Clamp terminal - 1 cable(s) 5 mm² - flexible
	Clamp terminal - 2 cable(s) 2.6 mm <sup>2</sup> - flexible with cable end
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-1	
Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4085 °C	

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.800 cm	
Package 1 Width	8.000 cm	
Package 1 Length	9.300 cm	
Package 1 Weight	78.000 g	
Unit Type of Package 2	BB1	

Number of Units in Package 2	8
Package 2 Height	8.800 cm
Package 2 Width	10.000 cm
Package 2 Length	26.600 cm
Package 2 Weight	679.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	6.604 kg

### Offer Sustainability

Green Premium product
☑ REACh Declaration
Compliant with Exemptions
Yes
☑ China RoHS Declaration
₽¥Yes
Product Environmental Profile
End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

	8 months
--	----------