Empty enclosure for switchgear

AKi-TE 425



AKi-TE 425

Empty enclosure for switchgear

Productnumber: 78942501
Dimensions: 300 x 600 x 210 mm

Switch disconnector enclosure with external actuation, lockable, 1 x load disconnector switch 250A, 3-pole switching, Screw connection M10, PE/N terminal M10, with insulating seals

with transparent cover

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Protection class:	II
Type of protection:	IP54/IP65
Rated current:	250 A
UL Type Rating:	not specified

Colours

Base unit colour:	grey
Cover colour:	transparent

Dimensions

Width:	300 mm
Length:	600 mm
Height:	210 mm
Weight:	6.73 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability:	850 °C (EN 60695-2-11)

mechanical properties

Impact strength:	IK08
Sealable:	yes

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C

Ambient conditions

Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Installation location:	protected outdoor areas

Sales Information

EAN:	4013902885626
ETIM Class:	EC000249
Custom tariff number:	85369095
Minimum order quantity:	1


Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

79300401 - AK ABL-ES - External fixing lugs

Cable gland


2x M20
2x M32/M40
1x M40/M50/
M63
4x M32/M40/
M50
4x M32/M40/
M50
2x M20
2x M32/M40
1x M40/M50/
M63