

SAIE-M23-L-RM**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



The M23 round plug-in connectors offer a high number of mating cycles, high current-carrying capacity and high contact-density coupled with minimum dimensions. Enclosures, inserts and crimp contacts need to be ordered separately.

General ordering data

| | |
|------------|--|
| Version | Sensor/Actuator plug-in connector, Built-in plugs, Empty enclosure |
| Order No. | 1170310000 |
| Type | SAIE-M23-L-RM |
| GTIN (EAN) | 4032248962358 |
| Qty. | 1 items |

SAIE-M23-L-RM

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



| | |
|-----------------------|----------------------------|
| ROHS | Conform |
| UL File Number Search | UL Website |
| Certificate No. (UR) | E344862 |

Dimensions and weights

| | |
|------------|------|
| Net weight | 33 g |
|------------|------|

Environmental Product Compliance

| | |
|--------------------------------------|--------------------------------------|
| RoHS Compliance Status | Compliant with exemption |
| RoHS Exemption (if applicable/known) | 6c |
| REACH SVHC | Lead 7439-92-1 |
| SCIP | 1c533b66-fcff-4da5-b89f-fd55fbf5cb55 |

Technical data customisable plug-in connectors

| | | | |
|------------------------------|-------------------|-------------------|-------------|
| Housing main material | Copper-zinc alloy | Protection degree | IP67, IP69K |
| Pollution severity | 3 | Shield connection | Yes |
| Temperature range of housing | -40...+125 °C | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC003556 | ETIM 9.0 | EC003556 |
| ETIM 10.0 | EC003556 | ECLASS 14.0 | 27-44-02-24 |
| ECLASS 15.0 | 27-44-02-24 | | |

SAIE-M23-L-RM

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

Drawings

www.weidmueller.com

Dimensioned drawing

