


date: 28/10/2026

GUELL 1+ S/W

Part number LTF1123DS840







IP 66 | CLASS I | FULL CUT OFF | ULR<1 | CIEn°3>95 | DALI | CE | EAC | UKCA

Description

LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10–Ø14 mm
- DALI dimmable
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001744

General information

Lampholder:	LED	**Light source:**	
Lightsource lumen output [lm]:	8262	**Luminaire lumen output [lm]:**	7070
Luminaire wattage [W]:	51 W	**Luminous efficacy [lm/W]:**	139
CRI:	80	**Colour temperature [K]:**	4000
Colour / Finishing:	GR-94 / Metallic grey / Textured	**IP degree of protection:**	IP66
Impact resistance / impact energy:	IK07 3J xx5	**Protection class:**	I
Optic:	S/W - Symmetric Wide	**Net weight [kg]:**	2.171
Overall length [mm]:	249	**Overall width [mm]:**	80
Overall height [mm]:	314		

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	Glass	**Glow wire test [°C]:**	650 °C
Frontal exposed area [m²]:	0.02	**Lateral exposed area [m²]:**	0.02
Top exposed area [m²]:	0.06		

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	0.9
Inrush current [A/µs]:	16 / 50	**C10 1.5 mm²:**	21
C16 2.5 mm²:	33	**B10 1.5 mm²:**	13
B16 2.5 mm²:	20		

Installation

Application area:	Outdoor lighting	**Mounting type:**	Professional floodlight
Min. ambient temperature [°C]:	-20	**Max. ambient temperature [°C]:**	35
Min. distance from lighted object [m]:	0.10		

Light features

MacAdam:	3	**Lumen maintenance:**	L80B10@160000h
Distribution of light emission:	Direct	**DFF - Downward Flux Fraction [%]:**	100
UFF - Upward Flux Fraction [%]:	0	**Luminous Intensity Class:**	G*6
Zero light pollution (ULR = 0%):		**IPEA* (road lighting):**	A7+
IPEA* (large areas, roundabouts):	A8+	**IPEA* (cycle-pedestrian):**	A7+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com


IPEA* (green areas):	A7+	**IPEA* (historic city centers):**	A12+

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories

GUELL 1+



LTF1A2112

Single pole top support GUELL 1+

GR-94 / Metallic grey



LTF1A2122

Double pole top support GUELL 1+

GR-94 / Metallic grey



14173394

Wall support 500 mm/19.69" GUELL 1/2

GR-94 / Metallic grey



14173494

Wall support 1000 mm/39.37" GUELL 1/2

GR-94 / Metallic grey

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com