
AS427 LED SPOT REFLECTOR

Part number 8427453333410







IP 20 | CLASS I

Description

LED track light for indoor, comprising:
- Extruded aluminium profile and die-cast aluminium spotlight housing, powder-coated
- Tilting and turning spotlight head
- High-brilliance spherical faceted reflector for maximum performance and neutral colour rendering index
- Bayonet-closure ring for a toolless replacement of the reflector and the louvre
- Reflector in Spot design
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Universal tri-phase adaptor included
- Built-in driver
- Quick and toolless installation
- Clear safety glass
- The luminaire is suitable for installation on standard tracks such as EUROSTANDARD PLUS®

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001744

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	4400	**Luminaire lumen output [lm]:**	3530
Luminaire wattage [W]:	35 W	**Luminous efficacy [lm/W]:**	101
CRI:	80	**Colour temperature [K]:**	4000
Colour / Finishing:	WH-RAL9010 / White RAL9010 / Textured	**IP degree of protection:**	IP20
Impact resistance / impact energy:	IK02 0.2J xx0	**Protection class:**	I
Optic:	C/I - Circular Intensive	**Beam angle:**	2 x 6°
Net weight [kg]:	1.447	**Overall diameter [mm]:**	125
Overall length [mm]:	150	**Overall width [mm]:**	125
Overall height [mm]:	250		

Mechanical features

Shape:	Round ≤ 150 mm	**Housing material:**	Aluminium
Diffuser material:	Transparent glass	**Glow wire test [°C]:**	650 °C

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	50/60	**Power factor / COS Φ:**	>0.9
C10 1.5 mm²:	36	**C16 2.5 mm²:**	63
B10 1.5 mm²:	22	**B16 2.5 mm²:**	38
EEI:	A2		

Installation

Application area:	Indoor lighting	**Mounting type:**	Tracklight
Min. ambient temperature [°C]:	10	**Max. ambient temperature [°C]:**	40
Min. distance from lighted object [m]:	0.10		

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@60000h
Distribution of light emission:	Direct	**DFF - Downward Flux Fraction [%]:**	100
UFF - Upward Flux Fraction [%]:	0		

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211


info.it@pil.lighting
www.performanceinlighting.com

Photometric data



Optional accessories

AS427 LED



8417900

Frosted safety glass pane



8435961

Food glass filter for meat products



8435962

Food glass filter for bakery products



8435963

Food glass filters for fruits and cheese



8435964

Food glass filter for vegetables



8435965

Food glass filter for fish products

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com