


SMALL LINE PL REFLECTOR

Part number 8726441583410







IP 20 | CLASS I | CE | EAC | UKCA | EN

Description

Suspended, LED luminaire for indoor, comprising:
- Extruded aluminium profile housing, die-cast aluminium end caps, steel sheet canopy, painted
- Slender plates with open spaces give the luminaire a uniquely delicate design
- Direct / indirect light distribution
- Gear tray with high-shine multifaceted reflectors (metallized with ultra-pure aluminium) for maximum luminaire efficiency and neutral colour rendering
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m) and canopy
- The luminaire unit is attached to the cable suspension without tools using clips
- Power is supplied via the cable suspension, no additional supply cable is required
- VDU application suitable acc. to EN 12464-1
- Special colour versions available. Consult factory
- Continuous mounted version at www.light-performer.com
- Design by BÜRO SOMMER
- Design by BÜRO SOMMER

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Product data

ETIM Group:	EG000027	**ETIM Class:**	EC001743

General information

Lampholder:	LED	**Light source:**	LED
Lightsource lumen output [lm]:	9770	**Luminaire lumen output [lm]:**	7400
Luminaire wattage [W]:	55 W	**Luminous efficacy [lm/W]:**	135
CRI:	80	**Colour temperature [K]:**	4000
Colour / Finishing:	WH-RAL9016 / White RAL9016 / Textured	**IP degree of protection:**	IP20
Impact resistance / impact energy:	IK03 0.35J xx1	**Protection class:**	I
Optic:	S/C - Symmetric direct-indirect	**Beam angle:**	2 x 37°
Net weight [kg]:	1.3	**Overall length [mm]:**	1256
Overall width [mm]:	132	**Overall height [mm]:**	26

Mechanical features

Shape:	Rectangular	**Housing material:**	Aluminium
Diffuser material:	No diffuser	**Glow wire test [°C]:**	650 °C

Electrical features

Voltage type:	AC	**Input voltage [V AC]:**	220/240
Input frequency [Hz]:	220-240V 50/60Hz	**Power factor / COS Φ:**	0.9
Input voltage [V DC]:	168/275	**Inrush current [A/µs]:**	20 / 240
C10 1.5 mm²:	24	**C16 2.5 mm²:**	40
B10 1.5 mm²:	15	**B16 2.5 mm²:**	24
EEI:	A2		

Installation

Application area:	Indoor lighting	**Mounting type:**	Suspended
Min. ambient temperature [°C]:	10	**Max. ambient temperature [°C]:**	40

Light features


MacAdam:	3	**Lumen maintenance:**	L80B10@50000h
Distribution of light emission:	Direct/Indirect	**DFF - Downward Flux Fraction [%]:**	40
UFF - Upward Flux Fraction [%]:	60	**UGR max.:**	8.0

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com

Photometric data



To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website www.performanceinlighting.com. Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25ºC. Terms of warranty are available at https://www.performanceinlighting.com/qr/company/led-warranty

For information:
PERFORMANCE iN LIGHTING S.p.A. Headquarters - Italy
Viale del Lavoro 9/11
37030 Colognola ai Colli Verona - Italy
Tel. +39 045 61 59 211

info.it@pil.lighting
www.performanceinlighting.com