



Hoofd

Range of product	Harmony
Product or component type	Kop voor controlelampje
Productspecifieke toepassing	Voor gloeilamp
Kap/operator of lenskleur	Groen

Complementair

Mechanical durability	1000000 cycles
Net weight	0,015 kg
Compatibility code	ZA2B

Omgeving

Standards	CSA C22.2 Nr 14 EN/IEC 60947-5-1
Beschermende behandeling	TH
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Trilling bestendigheid	15 gn (f= 10...500 Hz) conform aan IEC 60068-2-6
Schokbestendigheid	100 gn conform aan IEC 60068-2-27
Beschermingsklasse tegen elektrische schokken	Klasse II conform aan IEC 61140
Overvoltage category	Klasse II conform aan IEC 61140
IP beschermingsgraad	IP65 conforming to IEC 60529
IK-beschermingsgraad	IK08 conforming to EN 50102

Verpakkingseenheid

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,5 cm
Package 1 Width	4,0 cm
Package 1 Length	4,0 cm
Package 1 Weight	15,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5,0 cm
Package 2 Width	17,0 cm
Package 2 Length	15,0 cm
Package 2 Weight	152,0 g
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	15,0 cm

Package 3 Width	15,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	1,705 kg

Duurzaamheid van het aanbod

Duurzaamheids status van het aanbod	Green Premium product
REACH-regelgeving	REACH-verklaring
REACH vrij van SVHC	Ja
EU-richtlijn RoHS	Voldoet pro-actief (Product valt niet onder de EU RoHS juridische scope) EU-verklaring RoHS
Vrij van giftige zware metalen	Ja
Kwikvrij	Ja
RoHS-regulering China	RoHS-verklaring China
Informatie over RoHS-vrijstelling	Ja
Milieu Profiel	Milieuprofiel Van Het Product
Circulair Profiel	Informatie Over Einde Levensduur

contractuele waarborg

Garantie	18 months
----------	-----------