

PFXWRT100A

Web viewer license, Pro-face BLUE, version 3.x, entity, 100 station, permanent, runtime, add on



Presentazione

Gamma prodotto	Pro-face BLUE
Tipo prodotto	Licenza
Formato	Digital
Tipo software	Add-on
Tipo di licenza	Node locked license
Variante	Runtime
Versione software	V3.5
Operating system requirement	Windows 10 64 bit
Requisiti di sistema	8 GB RAM 30 GB hard-drive space
Lingua	Inglese Italiano Cinese Spagnolo Francese Tedesco Portoghese Coreano

Caratteristiche tecniche

License category	Permanent
Protocollo porta comunicazione	CANopen slave Couzet Automation millenium 3 FBD Emerson Industrial Automation Modbus SIO master Emerson Industrial Automation Modbus TCP master Control Techniques Modbus SIO master Control Techniques Modbus TCP master Emerson Process Management ROC Plus Ethernet Emerson Process Management ROC SIO Mitsubishi HTTP Mitsubishi IPsec Mitsubishi A series Ethernet Mitsubishi FX series CPU direct Mitsubishi FX series Ethernet Mitsubishi iQ-R/F series Ethernet SLMP client Mitsubishi Q series CPU direct Mitsubishi Q series QnU CPU Ethernet Mitsubishi Q/QnA series serial Modbus Organization Modbus SIO ASCII master Modbus Organization Modbus SIO master Modbus Organization Modbus SIO slave Modbus Organization Modbus TCP master Modbus Organization Modbus TCP slave Omron CS/CJ/CP series host link Omron CS/CJ/CP/NX series Ethernet Omron CS/CJ/NJ/NX series Ethernet/IP Rockwell Automation OPC UA server Rockwell Automation Profibus DP slave Rockwell Automation Ethernet/IP Rockwell Automation DF1 Rockwell Automation DH485 Schneider Electric Ethernet/IP via USB Schneider Electric Modbus SIO master Schneider Electric DF1 Schneider Electric Modbus TCP master Schneider Electric Modbus TCP master via USB Schneider Electric Machine expert network Schneider Electric PacDrive Schneider Electric Uni-Telway Schneider Electric Zelio Logic Siemens Simatic S7 Ethernet Siemens Simatic S7 MPI direct Siemens TIA portal Ethernet CoDeSys Automation Alliance websocket Azbil corporation Modbus TCP master Beckhoff Automation TwinCAT ADS/AMS CoDeSys Automation Alliance CoDeSys V2 Ethernet CoDeSys Automation Alliance CoDeSys V3 Ethernet Denso wave b-CAP Protocol Fanuc PowerMate series Fuji Electric MICREX-SX series Ethernet Fuji Electric Modbus SIO temperature controller GE Intelligent Platforms series 90 Ethernet GE Intelligent Platforms series 90-30/70 SNP-X JTEKT Toyopuc H series Ethernet Hitachi IES H series SIO Hitachi S10V series Ethernet IAI Corporation X-SEL Controller JTEKT Toyopuc CMP-LINK Ethernet JTEKT Toyopuc CMP-LINK SIO Keyence KV series Ethernet Keyence KV series SIO Keyence KV-10/16/24/40 CPU direct LS Electric GLOFA series Cnet LS Electric Master-K series Cnet LS Electric XGK series CPU direct LS Electric XGT/XGB series Cnet LS Electric XGT/XGB series FEnet Panasonic industrial Devices MEWTOCOL-COM Ethernet Pro-face by Schneider Electric memory link Ethernet Pro-face by Schneider Electric memory link SIO Sanmei Electronics Si/CutyAxis series SIO Shenzen Inovance Technology Modbus SIO master Shenzen Inovance Technology Modbus TCP master Shibaura Machine TC series(TCmini/TC200) Yaskawa Electric high speed Ethernet server Yaskawa Electric inverter/servo SIO Yaskawa Electric MP Ethernet/MECHATROLINK Yaskawa Electric MP Extension SIO Yokogawa Electric Modbus SIO master Yokogawa Electric Modbus TCP master

Compatibilità prodotto	Windows compatible PC
Compatibilità gamma	Pro-face SP5000 Pro-face ST6000 Pro-face STM6000 Pro-face 4100 Pro-face SP5000X Pro-face iPC
Hosting option	On-device
License size	Entity (100 station)
Processor requirement	Intel core i3 8th generation Intel core i5 8th generation
Risoluzione visualizzazione	320 x 240 pixels HVGA minimo 3840 x 2160 pixels 4K UHD massimo

Garanzia contrattuale

Garanzia	18 mesi
----------	---------