



## Main

|                                     |                                                                                                                        |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Device short name                   | MT250                                                                                                                  |
| Product or component type           | Motor mechanism                                                                                                        |
| Device application                  | Automatic spring charging                                                                                              |
| Range compatibility                 | ComPacT new generation ComPacT NSX250 new generation<br>ComPacT new generation ComPacT NSX DC new generation NSX250 DC |
| Control type                        | Standard                                                                                                               |
| [Uc] control circuit voltage        | 208...277 V AC 60 Hz<br>220...240 V AC 50/60 Hz                                                                        |
| Circuit breaker mounting mode       | Fixed                                                                                                                  |
| Circuit breaker frame rated current | 250 A                                                                                                                  |

## Complementary

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| Control signal type             | Maintained<br>Impulse                                    |
| Circuit breaker response time   | < 700 ms open<br>< 80 ms closed                          |
| Maximum operating frequency     | 4 per minute                                             |
| Maximum power consumption in VA | 500 VA closing<br>500 VA opening                         |
| Provided equipment              | SDE adaptor                                              |
| Locking options description     | 1 to 3 padlocks Ø 5 to Ø 8<br>Padlocking in OFF position |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 10.8 cm   |
| Package 1 Width              | 12.4 cm   |
| Package 1 Length             | 17.0 cm   |
| Package 1 Weight             | 1.39 kg   |
| Unit Type of Package 2       | S04       |
| Number of Units in Package 2 | 15        |
| Package 2 Height             | 30.0 cm   |
| Package 2 Width              | 40.0 cm   |
| Package 2 Length             | 60.0 cm   |
| Package 2 Weight             | 21.616 kg |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                   |
| Mercury free               | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| California proposition 65  | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>                  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|