

**HDC 24D KLU 1M25G****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**IP65**

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

|            |                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version    | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Coupling housing, End-locking clamp, lower side, high, Size of cable entries: M 25 |
| Order No.  | <a href="#">1787460000</a>                                                                                                                                  |
| Type       | HDC 24D KLU 1M25G                                                                                                                                           |
| GTIN (EAN) | 4032248204809                                                                                                                                               |
| Qty.       | 1 pc(s).                                                                                                                                                    |

## HDC 24D KLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Height     | 75 mm   | Height (inches) | 2.953 inch |
| Width      | 72.4 mm | Width (inches)  | 2.85 inch  |
| Net weight | 236 g   |                 |            |

## Temperatures

|                   |                   |
|-------------------|-------------------|
| Limit temperature | -40 °C ... 125 °C |
|-------------------|-------------------|

## Dimensions

|                      |           |                     |       |
|----------------------|-----------|---------------------|-------|
| Cable entry          | w. thread | Height of housing B | 75 mm |
| Total length housing | 73 mm     | Width housing C     | 43 mm |

## General data

|                             |                             |                       |                             |
|-----------------------------|-----------------------------|-----------------------|-----------------------------|
| EMC housings                | No                          | Housing main material | diecast aluminium           |
| Material of locking element |                             | Protection degree     | IP65 (in plugged condition) |
| Surface finish              | Stainless steel, rust-proof |                       |                             |
|                             | Powder coating              |                       |                             |

## Version

|                              |                               |                                |                    |
|------------------------------|-------------------------------|--------------------------------|--------------------|
| BG                           | 4                             | Cable entry                    | w. thread          |
| Clamp version                | End-locking clamp             | Colour (RAL)                   | RAL 7035           |
| Design                       | high                          | Design of housing              | Coupling housing   |
| Design of locking system     | End-locking clamp, lower side | Internal thread                | M 25               |
| Number of cable entry on top | 1                             | Number of cable entry sideways | 0                  |
| Sealing                      | NBR                           | Size                           | 4                  |
| Size of cable entries        | M 25                          | Suitable for ModuPlug®         | Yes                |
| Top part/bottom part/lid     | lower part                    | Type                           | coupling extension |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000437    | ETIM 7.0    | EC000437    |
| ETIM 8.0    | EC000437    | ETIM 9.0    | EC000437    |
| ETIM 10.0   | EC000437    | ECLASS 9.0  | 27-44-02-02 |
| ECLASS 9.1  | 27-44-02-02 | ECLASS 10.0 | 27-44-02-02 |
| ECLASS 11.0 | 27-44-02-02 | ECLASS 12.0 | 27-44-02-02 |
| ECLASS 13.0 | 27-44-02-02 | ECLASS 14.0 | 27-44-02-02 |
| ECLASS 15.0 | 27-44-02-02 |             |             |

|                     |                         |
|---------------------|-------------------------|
| Substance           | Acetone                 |
| Chemical resistance | Conditionally resistant |
| Substance           | Drilling oil            |
| Chemical resistance | Resistant               |
| Substance           | Diesel                  |
| Chemical resistance | Resistant               |
| Substance           | Ethyl alcohol           |
| Chemical resistance | Resistant               |
| Substance           | Transmission oil        |

## HDC 24D KLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

|                     |                         |
|---------------------|-------------------------|
| Chemical resistance | Resistant               |
| Substance           | Hydraulic oil           |
| Chemical resistance | Resistant               |
| Substance           | Coolant                 |
| Chemical resistance | Resistant               |
| Substance           | Petroleum benzine       |
| Chemical resistance | Resistant               |
| Substance           | Sweat                   |
| Chemical resistance | Resistant               |
| Substance           | Premium gasoline        |
| Chemical resistance | Conditionally resistant |
| Substance           | Water                   |
| Chemical resistance | Resistant               |
| Substance           | UV                      |
| Chemical resistance | Unstable                |
| Substance           | Ozone                   |
| Chemical resistance | Unstable                |

## Environmental Product Compliance

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoHS Compliance Status | Compliant without exemption                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| REACH SVHC             | Potassium perfluorobutane sulfonate 29420-49-3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| SCIP                   | e98b2b24-ba23-41bf-8d19-Odda3647412f                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Chemical resistance    | de.myview.objectmodel.impl.BlockImpl@21e7bc3b de.myview.objectmodel.impl.BlockImpl@21b723c4<br>de.myview.objectmodel.impl.BlockImpl@6676260e de.myview.objectmodel.impl.BlockImpl@24b4bfe9<br>de.myview.objectmodel.impl.BlockImpl@382ed920 de.myview.objectmodel.impl.BlockImpl@201f64e2<br>de.myview.objectmodel.impl.BlockImpl@778e70b9 de.myview.objectmodel.impl.BlockImpl@7644d256<br>de.myview.objectmodel.impl.BlockImpl@386de267 de.myview.objectmodel.impl.BlockImpl@638eb9fc<br>de.myview.objectmodel.impl.BlockImpl@6701068c de.myview.objectmodel.impl.BlockImpl@3787ae58<br>de.myview.objectmodel.impl.BlockImpl@602e1c15 |

## Approvals

Approvals



|                         |                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approvals MAMID         | <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319222/-T1z1mm-S800/</a> <a href="https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/">https://mdcop.weidmueller.com/mediadelivery/rendition/900_319230/-T1z1mm-S800/</a> |
| ROHS                    | Conform                                                                                                                                                                                                                                                                                                                                                 |
| UL File Number Search   | UL Website                                                                                                                                                                                                                                                                                                                                              |
| Certificate No. (cURus) | E92202                                                                                                                                                                                                                                                                                                                                                  |

## HDC 24D KLU 1M25G

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

### Downloads

Approval/Certificate/Document of Con-  
formity

[Manufacturer's declaration](#)

Engineering Data

[CAD data – STEP](#)

Product Change Notification

[20220214 Technical change to HDC housings](#)

[20220214 Technische Änderung bei HDC-Gehäusen](#)

Catalogues

[Catalogues in PDF-format](#)

Brochures

[FL FIELDWIRING EN](#)


[FL FIELDWIRING EN](#)

### HDC 24D KLU 1M25G

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



## HDC 24D KLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Hood, Cable Entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

## General ordering data

|            |                            |                                                                                                                                 |
|------------|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Type       | HDC 10B TOLU 1M25G         | Version                                                                                                                         |
| Order No.  | <a href="#">1787620000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204960              | lower side, Standard, Size of cable entries: M 25                                                                               |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |
| Type       | HDC 10B TOLU 1PG16G        | Version                                                                                                                         |
| Order No.  | <a href="#">1655320000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408329              | lower side, Standard, Size of cable entries: PG 16                                                                              |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |
| Type       | HDC 24D TOLU 1PG21G        | Version                                                                                                                         |
| Order No.  | <a href="#">1655360000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408367              | lower side, high, Size of cable entries: PG 21                                                                                  |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |
| Type       | HDC 24D TOLU 1M25G         | Version                                                                                                                         |
| Order No.  | <a href="#">1787340000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204687              | lower side, high, Size of cable entries: M 25                                                                                   |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |
| Type       | HDC 24D TOLU 1PG29G        | Version                                                                                                                         |
| Order No.  | <a href="#">1655380000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408381              | lower side, high, Size of cable entries: PG 29                                                                                  |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |
| Type       | HDC 24D TOLU 1M32G         | Version                                                                                                                         |
| Order No.  | <a href="#">1787330000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from top, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204670              | lower side, high, Size of cable entries: M 32                                                                                   |
| Qty.       | 1 pc(s).                   |                                                                                                                                 |

## HDC 24D KLU 1M25G

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Accessories

## Hood, Cable Entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

## General ordering data

|            |                            |                                                                                                                                  |
|------------|----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Type       | HDC 10B TSLU 1PG16G        | Version                                                                                                                          |
| Order No.  | <a href="#">1655210000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408213              | lower side, Standard, Size of cable entries: PG 16                                                                               |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |
| Type       | HDC 24D TSLU 1M32G         | Version                                                                                                                          |
| Order No.  | <a href="#">1787270000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204618              | lower side, high, Size of cable entries: M 32                                                                                    |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |
| Type       | HDC 10B TSLU 1M25G         | Version                                                                                                                          |
| Order No.  | <a href="#">1787580000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204922              | lower side, Standard, Size of cable entries: M 25                                                                                |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |
| Type       | HDC 24D TSLU 1M25G         | Version                                                                                                                          |
| Order No.  | <a href="#">1787280000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4032248204625              | lower side, high, Size of cable entries: M 25                                                                                    |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |
| Type       | HDC 24D TSLU 1PG21G        | Version                                                                                                                          |
| Order No.  | <a href="#">1655250000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408251              | lower side, high, Size of cable entries: PG 21                                                                                   |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |
| Type       | HDC 24D TSLU 1PG29G        | Version                                                                                                                          |
| Order No.  | <a href="#">1655270000</a> | HDC enclosures, Size: 4, Protection degree: IP65 (in plugged condition), Cable entry from side, Plug housing, End-locking clamp, |
| GTIN (EAN) | 4008190408275              | lower side, high, Size of cable entries: PG 29                                                                                   |
| Qty.       | 1 pc(s).                   |                                                                                                                                  |