

## VG 29-MS68

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Similar to illustration



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

### General ordering data

Version	VG MS (standard brass cable gland), Cable glands, straight, PG 29, 8 mm, OD min. 18 - OD max. 25 mm, IP67, IP68 - 5 bar (30 min.), Brass, nickel-plated
Order No.	<a href="#">1569120000</a>
Type	VG 29-MS68
GTIN (EAN)	4008190176419
Qty.	10 items

## VG 29-MS68

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Technical data

## Approvals

Approvals



ROHS Conform

## Dimensions and weights

Height	48.5 mm	Height (inches)	1.9094 inch
Length	46.5 mm	Length (inches)	1.8307 inch
Net weight	131 g		

## Temperatures

Operating temperature -40 °C...100 °C

## Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	b5ff1f66-ddba-4739-9fc0-0521ddb52139

## Certificate numbers cable gland

Certificate no. cable gland (GERMLLOYD)	E-14047	Certificate no. cable gland (UL)	E-199260
Certificate no. cable gland (cULus)	E-199260	Approval conditions	DNV, UL, cULus

## General information

Outer cable diameter, max.	25 mm	Outer cable diameter, min.	18 mm
O-Ring	NBR	Protection degree with GWDR	IP67, IP68 - 5 bar (30 min.)
Tightening torque	15 Nm	Operating temperature range, max.	100 °C
Operating temperature range, min.	-40 °C	Pitch of thread	1.59 mm
Halogen	Yes	AF size 1	40 mm
AF size 2	40 mm	AF size	40 mm
Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Cable gland	PG, PG 29
Basic material	Brass, nickel-plated	Seal insert	CR
Sealing	NBR	External thread	PG 29
Length of thread	8 mm	Torque for cap nut, max.	31.00 Nm
Protection class (UL)	Type 4X	Torque for connecting adapter, max.	15.50 Nm
Torque for connecting adapter, min.	14.50 Nm	Torque for cap nut, min.	29.00 Nm
Clamp insert	Polyamide		

## Classifications

ETIM 8.0	EC000441	ETIM 9.0	EC000441
ETIM 10.0	EC000441	ECLASS 14.0	27-14-08-01
ECLASS 15.0	27-14-08-01		

**VG 29-MS68**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Accessories**

**Brass lock nuts, nickel-plated**



In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

Type	SKMU PG29-MS	Version	
Order No.	<a href="#">1719210000</a>	SKMU MS (brass locknut), Locknut, PG 29, 4 mm, Brass, nickel-plated	
GTIN (EAN)	4008190352431		
Qty.	50 ST		

**Neoprene flat gasket - GWDR NP**



In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

Type	GWDR PG29-NP	Version	
Order No.	<a href="#">1719600000</a>	GWDR NP (flat gasket - neoprene), Sealing ring, PG 29, Neoprene	
GTIN (EAN)	4008190352868		
Qty.	50 ST		

**Polyethylene flat gasket - GWDR PO**



In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

**General ordering data**

Type	GWDR PG29-PO	Version	
Order No.	<a href="#">1719500000</a>	GWDR PO (flat gasket - polyethylene), Sealing ring, PG 29,	
GTIN (EAN)	4008190352769	Polyethylene	
Qty.	50 ST		